

CORNER NOTES

LIST OF SURVEY DOCUMENTS USED FOR REFERENCE
RECORDING INFORMATION REFERS TO THE RECORDS OF THE SKAGOT COUNTY AUDITOR, UNLESS OTHERWISE NOTED.

- (1) OLD FIELD NOTES OF THE SUBDIVISION OF TOWNSHIP 33 NORTH, RANGE 6 EAST BY U.S. DEPUTY SURVEYOR ALEX M. REYNOLDS UNDER HIS CONTRACT NO. 354, COMPLETED IN SEPTEMBER 1891
- (2) PLAT OF LAKE CAYMAUGH SUBDIVISION NO. 1 BY HOWARD SEEVER, PROFESSIONAL ENGINEER, RECORDED IN VOLUME 5 OF PLATS, PAGES 57-62 AND DATED 8-28-1949
- (3) SECTION CORNER SHEET FOR SECTION 26 HELD AT THE DNR (NORTHWEST) REGION OFFICE IN SERVO-WOODLEY, UNDATED
- (4) SECTION CORNER SHEET FOR SECTION 23 HELD AT THE DNR (NORTHWEST) REGION OFFICE IN SERVO-WOODLEY, UNDATED
- (5) GEORGIA PACIFIC WORKMAP IN SECTIONS 15,21,22,23,26, ON FILE WITH THE DNR PUBLIC LAND SURVEY OFFICE IN QUIMPIA, UNDATED
- (6) CRUISER'S FIELDBOOK #42 ("SECTION LINES LAKE CAYMAUGH"), FROM THE G.P. COLLECTION RECEIVED BY THE DNR PUBLIC LAND SURVEY OFFICE IN 2005, DATED 1988
- (7) GEORGIA PACIFIC FIELDBOOK 178 (LAKE CAYMAUGH TRANSIT TRAILERS), ON FILE WITH THE DNR PUBLIC LAND SURVEY OFFICE IN QUIMPIA, DATED 1934-1937
- (8) RECORD OF SURVEY IN SECTION 25 BY MICHAEL MONMOR & ASSOCIATES, P.L.S. (SECTION 25), RECORDED UNDER AFN 5910303014 AND DATED 10-3-1995
- (9) RECORD OF SURVEY IN SECTION 28 BY WATSON AND ASSOCIATES INC. (THOMAS SPERRY PLAT), RECORDED UNDER AFN 200210250164 AND DATED 10-25-2002
- (10) SHORT PLAT NO. 05-0916 IN SECTION 25 BY AZIMUTH NORTHWEST INC. (STUART B. VAN BIRN, P.L.S. 21591), RECORDED UNDER AFN 200612080121 AND DATED 12-8-2006
- (11) RECORD OF SURVEY IN SECTION 25 BY LISSER & ASSOCIATES (BRUCE G. LISSER, P.L.S. 22989), RECORDED UNDER AFN 200711130040 AND DATED 11-13-2007

(LMI) PLAT MONUMENT SET ON PLAT PERMETER

ACCEPTED IRON PIPE

HISTORY: 1946-PLAT SHOWS THE SYMBOL FOR AN IRON PIPE(2) UNDATED-SECTION CORNER SHEET SHOWS A POSITION, APPARENTLY CALCULATED FROM 1946 PLAT(5) 2002-RECORD OF SURVEY SETS A FOUND 1" IRON PIPE(9) FIELD SEARCH: WE FOUND AN OLD 1.5" IRON PIPE ACCEPTED AS 1946 PLAT MON. SET SHEET 1" FOR RELATIONSHIP TO NORTHERLY CORNER OF LOT 1.

(R19) QUARTER CORNER COMMON TO SECTIONS 23 & 26

ACCEPTED IRON PIPE

HISTORY: UNDATED-SECTION CORNER SHEET SHOWS AN IRON PIPE(2) UNDATED-GEORGE WORKMAP SHOWS AN IRON PIPE(4) 1946-SECTION CORNER SHEET SHOWS A FOUND PIPE AND STAKE(8) 1995-RECORD OF SURVEY SETS A FOUND 1.5" IRON PIPE, 4" TALL(7) FIELD SEARCH: WE FOUND AND ACCEPTED A 1" IRON PIPE WITH 2" ALUMINUM CAP MARKED WITH CORNER DESIGNATION AND DIMENSION LS 21423 1998. A 5' LONG 1.5" IRON PIPE IS LAID ALONG SIDE PERPETUATION: A 23" HEADLOCK BEARS N84° AT 18.03 FEET TO AN ALUMINUM NAIL THAT IS 1.5" UP ON THE SOUTH SIDE NAIL THAT IS 2" UP ON THE WEST SIDE AN 80" CEDAR STUMP BEARS N71°W AT 63.82 FEET TO A STEEL NAIL THAT IS 3" UP ON THE NORTHEAST SIDE NAIL THAT IS 2" UP ON THE SOUTHWEST SIDE SET CASSINITE POST 1" SOUTH FIELDBOOK 716, PAGE 18

(R21) SECTION CORNER COMMON TO SECTIONS 23, 24, 25, 26

REPLACED IRON PIPE WITH ALUMINUM MONUMENT

HISTORY: UNDATED-SECTION CORNER SHEET SHOWS 1" IRON PIPE(2) UNDATED-GEORGE WORKMAP SHOWS A POSITION, APPARENTLY CALCULATED FROM 1946 PLAT(5) FIELD SEARCH: ON 1-10-2018, WE FOUND A 1.5" IRON PIPE, 4.4' LONG, WITH WELDED TIP (THE DISTINCTIVE TYPE USED BY ENGLISH LUMBER CO., LAMENED OVER), AND TWO DIVISION OF FORESTRY TAGS IN THE 67" CEDAR STUMP 58'-50" FROM A DECKING FROM THE MONUMENT. A 60" CEDAR STUMP BEARS S84°E AT 76.02 FEET TO A STEEL NAIL THAT IS 2" UP ON THE SOUTHWEST SIDE. WE STOOD PIPE BACK UP OVER ITS BASE AND CHECKED THE POSITION (GROUND), THEN REPLACED THE PIPE WITH AN ALUMINUM MONUMENT. PERPETUATION: A 93" FIR SNAG BEARS NORTH AT 88.98 FEET TO A STEEL NAIL THAT IS 4" UP ON THE WEST SIDE NAIL THAT IS 1" UP ON THE SOUTHEAST SIDE A 70" CEDAR STUMP BEARS S44°E AT 76.02 FEET TO A STEEL NAIL THAT IS 2" UP ON THE SOUTHWEST SIDE NAIL THAT IS 1.5" UP ON THE NORTHEAST SIDE SET CASSINITE POST 1" WEST FIELDBOOK 716, PAGE 3

(S19) CENTER NORTH SIXTEENTH CORNER OF SECTION 26

REPLACED IRON PIPE WITH ALUMINUM MONUMENT

HISTORY: UNDATED-SECTION CORNER SHEET SHOWS A POSITION, APPARENTLY CALCULATED FROM 1946 PLAT(5) FIELD SEARCH: ON 2-12-2018, WE FOUND AN OLD 1" IRON PIPE WITH PLUG AND ACCEPTED AS 1946 PLAT MON. SET SHEET 1" FOR RELATIONSHIP TO CORNER OF LOT 1. (MAGSIBER, GRD) VS. 416.3 (PLAT), BUT WE FOUND NO OTHER PIPES IN EITHER POSITION AND THINK IT POSSIBLE THAT THE 1946 PIPES WERE STUBBED PLATED BLOCK BOUNDARIES INTO THESE EXTENSION LINES. WE ACCEPTED THIS PIPE AS THE 1946 PLAT MONUMENT AT CORNER S19 AND REPLACED IT WITH AN ALUMINUM MONUMENT. PERPETUATION: STUMP BEARS W24° AT 22.77 FEET TO A STEEL NAIL THAT IS 2" UP ON THE SOUTHEAST SIDE A 14" HEADLOCK BEARS S78°E AT 44.89 FEET TO AN ALUMINUM NAIL THAT IS 1" UP ON THE SOUTHWEST SIDE NAIL THAT IS 1" UP ON THE SOUTHWEST SIDE A 19" HEADLOCK BEARS N25°W AT 17.15 FEET TO AN ALUMINUM NAIL THAT IS 1" UP ON THE NORTHEAST SIDE SET CASSINITE POST 1" NORTHEASTLY FIELDBOOK 716, PAGE 11

(S21) NORTH SIXTEENTH CORNER COMMON TO SECTIONS 26 & 28

SET ALUMINUM MONUMENT

HISTORY: UNDATED-SECTION CORNER SHEET SHOWS A POSITION, APPARENTLY CALCULATED FROM 1946 PLAT(5) FIELD SEARCH: ON 2-6-2018, WE TIED THE 2002 WITNESS CORNER BEAR (LS 28867) AND FOUND IT TO BE 526'-00"-01W 01R (GRD) FROM OUR 121'. AS WE HAD THE BENEFIT OF A DIRECT LINE TO BOTH CONTROLLING CORNERS AND AN INTEREST IN MONUMENTING THE DISTINGUISHING THE SITUATION WITH THOMAS BERRY PIPES 2007/2008 4-3-2018, WE REMOVED HIS BEAR AND SET A 5/8" BEAR WITH ALUMINUM CAP AT OUR CALCULATED MOUNT AS THE NORTH 1/16. PERPETUATION: A 6" HEADLOCK BEARS W24° AT 28.17 FEET TO AN ALUMINUM NAIL THAT IS 1.5" UP ON THE SOUTHWEST SIDE A 9" CEDAR BEARS N49°W AT 26.55 FEET TO AN ALUMINUM NAIL THAT IS 2" UP ON THE SOUTHWEST SIDE SET CASSINITE POST 1" NORTH FIELDBOOK 716, PAGE 24

(T21) QUARTER CORNER COMMON TO SECTIONS 25 & 26

ACCEPTED BEAR AND CAP

HISTORY: UNDATED-SECTION CORNER SHEET SHOWS A PILE(2) 1995-RECORD OF SURVEY SETS A CALCULATED POSITION(8) 2002-RECORD OF SURVEY SETS 5/8" BEAR AT CALCULATED POSITION FROM 1946 PLAT(5) FIELD SEARCH: WE FOUND AND ACCEPTED A 5/8" BEAR WITH YELLOW PLASTIC CAP (MELTON, LS 28687) WE ALSO FOUND THE PLAT MONUMENT (WITH BEAR AND CAP DRIVEN INSIDE IN 1995(8), WHICH IS 88919-531' AT 241.07' (GRD). PERPETUATION: A 15" CEDAR BEARS N42° AT 22.09 FEET TO AN ALUMINUM NAIL THAT IS 1.5" UP ON THE SOUTHWEST SIDE NAIL THAT IS 1.5" UP ON THE SOUTHWEST SIDE A 17" CEDAR BEARS S64°W AT 8.29 FEET TO AN ALUMINUM NAIL THAT IS 3" UP ON THE SOUTHWEST SIDE SET CASSINITE POST 1" NORTH FIELDBOOK 716, PAGE 26

(V23) QUARTER CORNER COMMON TO SECTIONS 25 & 36

ACCEPTED IRON PIPE UNDER ROADWAY

HISTORY: 1946-PLAT SHOWS THE SYMBOL FOR AN IRON PIPE(2) ASPHALT ROAD(3) SURVEY SHOWS A 1.75" IRON PIPE 1.2' BELOW 2008-SHORT PLAT FINDS A 1.5" IRON PIPE(10) 2007-RECORD OF SURVEY FINDS A PIPE BELOW ROAD SURFACE(11) FIELD SEARCH: ON 3-27-2018 WE FOUND AND ACCEPTED A 31.5" IRON PIPE, 1.3" DIA. WITH 2" CAP AND 1.5" DIA. CAP. THE MONUMENT IS AT 821' DRIVE. THIS IS AN OLD PIPE, POSSIBLY FROM THE ENGLISH LUMBER COMPANY. OUR MEASURED DISTANCE FROM THE MONUMENT AT B21 MCASURE = 5904.07' (GRD). THE PLAT MONUMENT REQUIRED TO GRD = 5904.40'. THIS PIPE NOW HAS A MONUMENT CASE INSTALLED OVER IT THANKS TO THE SKAGOT COUNTY SURVEY DEPARTMENT.



A SURVEY OF THE NORTH HALF OF THE
NORTHEAST QUARTER SECTION 26, T33N, R06E, W1M.

STATE OF WASHINGTON
DEPARTMENT OF NATURAL RESOURCES

LAND SURVEY SECTION-P.O. BOX 47030
OLYMPIA, WASHINGTON 98504-7030 (360)902-1206

"BUTLERS BOWL" SURVEY	FIELD CREW: B. WILLIAMS, P.L.S.
FIELD BOOK: 716	M. BECKETT
5/10/2018	M. JANSSEN, L.S.T.

F.M.# 2020
SHEET 2 OF 2