

LIST OF PERTINENT SURVEY DOCUMENTS USED FOR REFERENCE
RECORDING INFORMATION REFERS TO THE RECORDS OF THE SNAIGT
COUNTY ARCHIVES

- (1) GENERAL LAND OFFICE SURVEY BY U.S. GEORGY SURVEYOR JAMES TILSON SHEETS, UNDER HIS CONTRACT NUMBER 305, DATED 3-27-1884
- (2) GENERAL LAND OFFICE SURVEY BY U.S. GEORGY SURVEYOR WINDOM T. SPERAN, UNDER HIS CONTRACT NUMBER 424, DATED 0-29-1893
- (3) GENERAL LAND OFFICE SURVEY BY U.S. TRANSIT MAN H.N. SUPERINTENDENT SPECIAL INSTRUCTIONS DATED 2/21/1914 AND SUPPLEMENTED 0-6-1912
- (4) DNR SECTION CORNER SHEET FOR SECTION 4, T14N, R10E, NORTHEAST REGION OFFICE IN SEMINOOLEE, AND ON FILE WITH THE DNR PUBLIC LAND SURVEY OFFICE IN OLVMPWA, FERMINT DATE OF 1929
- (5) DNR RIGHT OF WAY PLAT IN SECTION 5 BY WILLIAM G. MURDOCK, OLVMPWA AND DATED 2-23-1917
- (6) RECORD OF SURVEY IN SECTION 4 BY QUINCY R. VAN COTT, PLS 18657, RECORDED UNDER AYN #6688 AND DATED 1-10-1917
- (7) RECORD OF SURVEY IN SECTION 4 BY RICHARD AND LEONARD G. ASSOCIATES (HAROLD P. HARPER, PLS 6762, RECORDED UNDER AYN #6999 AND DATED 7-6-1917
- (8) DNR FINAL MAP #293 IN SECTIONS 9 AND 16, BY HERBERT L. HEMENWAY, PLS 8771, ON FILE WITH THE DNR PUBLIC LAND SURVEY OFFICE IN OLVMPWA AND DATED 10-9-1917
- (9) RECORD OF SURVEY IN SECTION 5 ROGER AND LEONARD G. #68189 AND DATED 11-2-1917
- (10) LAND CORNER RECOVERY FOR CORNER 829 BY HERBERT L. HEMENWAY, PLS 8771, RECORDED UNDER AYN #6917 AND DATED 11-16-1917
- (11) SHORT PLAT NUMBER 91-77 BY JOHN E. LEONARD, PLS 8982, RECORDED UNDER AYN #7179 AND DATED 1-11-1918
- (12) U.S. FOREST SERVICE CORNER SHEET FOR CORNER 827 BY R. O'CONNOR AND DATED 4-1919
- (13) SEATTLE CITY LIGHT F.B. #123-C SHOWING CONCRETE AND PWS CORNER MARKER ON FILE WITH THE DNR PUBLIC LAND SURVEY OFFICE IN OLVMPWA AND DATED 09-1984
- (14) DOT FIELDBOOK SHOWING CORNER RECOVERY OF CORNER 828 ON FILE WITH THE DNR PUBLIC LAND SURVEY OFFICE IN OLVMPWA AND DATED 9-1984
- (15) DOT FIELDBOOK SHOWING CORNER RECOVERY OF CORNER 829 ON FILE WITH THE DNR PUBLIC LAND SURVEY OFFICE IN OLVMPWA AND DATED 9-1984
- (16) RECORD OF SURVEY IN SECTION 5 BY OYAK (KEITH L. DAMANN, PLS 30449), RECORDED UNDER AYN #8047060 AND DATED 4-17-1988
- (17) RECORD OF SURVEY IN SECTIONS 5, 6, 31, 32 BY THE DEPT. OF TRANSPORTATION JAMES E. VAN PARYS, PLS 34673, RECORDED UNDER AYN #804981939 AND DATED 4-25-2008

CORNER NOTES

CORNER COORS REFER TO TOWNSHIP 33 NORTH, RANGE 10 EAST

(C67) CENTER QUARTER CORNER OF SECTION 5

REPLACED EXISTING 1/2" REBAR & CAP WITH ALUMINUM MONUMENT
HISTORY:
RECORD OF SURVEY SUBDIVIDES SECTION 5 AND SETS AN IRON ROD WITH YELLOW CAP FOR CENTER 1/4 Q
FIELD SEARCH:
ON 4-15-2022 WE TIED AND ACCEPTED A 1/2" REBAR WITH A FACED BROKEN YELLOW CAP (LEGIBLE) FLUSH WITH THE GROUND. WE REPLACED THE REBAR WITH 3/4" CAP MARKED WITH CORNER DESIGNATION, LS 15913 AND THE YEAR 2022. UP 0.5'
- A 17" HEALDOCK BEARS N52°E AT 41.81 FEET TO A STEEL NAIL
- AN 11" HEALDOCK BEARS S52°E AT 20.23 FEET TO A STEEL NAIL THAT IS 1.5' UP ON THE EAST SIDE
- A 2" FIBER BEARS S52°E AT 1.00 FEET TO A STEEL NAIL THAT IS 2.0' UP ON THE NORTHWEST SIDE
- A 2" HEALDOCK BEARS N27°W AT 46.44 FEET TO A STEEL NAIL THAT IS 2' UP ON THE NORTHEAST SIDE
SET CASSINITE POST 1' NORTH
FIELDBOOK 7151, PAGE 53

(C68) CENTER EAST 1/4 CORNER OF SECTION 5

SET ALUMINUM MONUMENT
HISTORY:
1986-DNR SECTION CORNER SHEET INDICATES THAT A PIPE WAS SET AT THIS CORNER. THE CORNER WAS FOUND BY THE SURVEYOR AND THE PIPE WAS LIKELY USED IN THE ESTABLISHMENT OF THE PILES LOCATION. (4) SUGGEST THAT METHODS OTHER THAN LEGITIMATE SURVEY METHODS WERE USED TO SUBDUDE THE SECTION (5)
FIELD SEARCH:
ON 4-27-2022, WE SET A 1/4" ALUMINUM BERTHSEN MONUMENT WITH 3/4" ALUMINUM DISC AT OUR CALCULATED POSITION WHICH FALLS IN THE SOUTHWEST EDGE OF AN OLD GRAVEL ROAD, 0.1' BELOW GRADE
PERFECTION:
- A 2" FIBER BEARS N52°E AT 18.82 FEET TO A STEEL NAIL
- A 2" FIBER BEARS S52°E AT 33.89 FEET TO A STEEL NAIL THAT IS 2' UP ON THE WEST SIDE
- A 4" CEAD BEARS S52°E AT 1.00 FEET TO A STEEL NAIL THAT IS 2' UP ON THE EAST SIDE
- A 1" UP ON THE EAST SIDE
- A 1" UP ON THE EAST SIDE
FIELDBOOK 7151, PAGE 59

(C69) QUARTER CORNER COMMON TO SECTIONS 4 & 5

ACCEPTED CONCRETE MONUMENT WITH BRASS DISC
HISTORY:
1987-DNR CORNER SHEET SHOWS 1' BT FOUND BY EMPLOYEE WCD (GONZALEZ/ET/AL) ON 4-18-2022, WE FOUND ONE BRASS DISC IN CONCRETE (MARKED WITH CORNER DESIGNATION AND THE YEAR 1984/14)
FIELD SEARCH:
ON 4-18-2022, WE TIED AND ACCEPTED A 3/4" CONCRETE MONUMENT, 0.4' ABOVE GRADE, WITH A 3/4" DIAMETER DNR BRASS DISC STAMPED WITH CORNER DESIGNATION AND THE YEAR 1984/14. THE MONUMENT AND OLD 2" PIPE IS JAMMED ONTO THE TOP OF THE 1' POST, 18" FR BT STUMP REMAINS, WITH VERGEL (CONCRETE), ONE WH 1.9' TO CENTER.
PERFECTION:
- A 12" CEAD BEARS S40°W AT 10.66 FEET TO A STEEL NAIL THAT IS 2.2' UP ON THE NORTHWEST SIDE
- A 12" HEALDOCK BEARS N27°W AT 33.90 FEET TO A STEEL NAIL THAT IS 2' UP ON THE NORTH SIDE
- A 12" HEALDOCK BEARS N27°W AT 37.70 FEET TO A STEEL NAIL THAT IS 0.6' UP ON THE EAST SIDE
SET CASSINITE POST 1' NORTH
FIELDBOOK 7151, PAGE 23

(D07) CENTER SOUTH 1/4 CORNER OF SECTION 5

SET ALUMINUM MONUMENT
HISTORY:
1977-RECORD OF SURVEY SUBDIVIDES SECTION 5 AND SETS AN IRON ROD WITH YELLOW CAP FOR C.S. 1/4 CORNER (7)
FIELD SEARCH:
RESEARCHED FOR BUT DID NOT FIND THE 1977 IRON ROD WITH CAP. THE AREA AROUND THE CORNER WAS SEARCHED AND FOUND A 1/2" REBAR WITH A FACED BROKEN YELLOW CAP (LEGIBLE) FLUSH WITH THE GROUND. WE REPLACED THE REBAR WITH 3/4" CAP MARKED WITH CORNER DESIGNATION, LS 15913 AND THE YEAR 2022. UP 0.5'
- A 17" HEALDOCK BEARS N52°E AT 41.81 FEET TO A STEEL NAIL THAT IS 1.5' UP ON THE EAST SIDE
- AN 11" HEALDOCK BEARS S52°E AT 20.23 FEET TO A STEEL NAIL THAT IS 1' UP ON THE NORTHWEST SIDE
- A 2" FIBER BEARS S52°E AT 1.00 FEET TO A STEEL NAIL THAT IS 2' UP ON THE NORTHEAST SIDE
- A 2" HEALDOCK BEARS N27°W AT 46.44 FEET TO A STEEL NAIL THAT IS 2' UP ON THE NORTHEAST SIDE
SET CASSINITE POST 1' NORTH
FIELDBOOK 7151, PAGE 65

(D08) SOUTHEAST 1/4 CORNER OF SECTION 5

SET ALUMINUM MONUMENT
HISTORY:
1987-DNR SECTION CORNER SHEET INDICATES THAT A PIPE WAS SET AT THIS CORNER. THE NAME ASSOCIATED WITH THIS WORK, TOGETHER WITH THE EARLIER RECORDS OF SURVEY, INDICATE THAT THE CORNER WAS ESTABLISHED BY THE 1927-DNR RIGHT OF WAY PLAT SHOWS A PIPE BUT DOESN'T SHAVE IF OR HOW THEY SUBDUDED THE SECTION (5)
FIELD SEARCH:
ON 4-27-2022, WE SET A 1/4" ALUMINUM MONUMENT WITH 3/4" ALUMINUM DISC, MARKED WITH CORNER DESIGNATION, LS 15913 AND THE YEAR 2022. UP 0.6'
PERFECTION:
- A 2" FIBER BEARS N52°E AT 21.53 FEET TO A STEEL NAIL THAT IS 1.5' UP ON THE WEST SIDE
- A 2" FIBER BEARS S52°E AT 20.23 FEET TO A STEEL NAIL THAT IS 2' UP ON THE NORTHWEST SIDE
- A 2" FIBER BEARS S41°E AT 3.99 FEET TO A STEEL NAIL THAT IS 1.5' UP ON THE EAST SIDE
- A 1" UP ON THE EAST SIDE
SET CASSINITE POST 2' NORTH
FIELDBOOK 7151, PAGE 67

(E07) QUARTER CORNER COMMON TO SECTIONS 5 & 8

ACCEPTED IRON PIPE
HISTORY:
1987-DNR SECTION CORNER SHEET SHOWS A FOUND 0.0' CEAD BT SNAO AND SETS A 1-1/4" PIPE WITH PLUG AND TACK, UP 2" IN A SMALL (6)
1977-RECORDS OF SURVEY FIND AND ACCEPT 1-1/4" IRON PIPE, UP 2" WITH PLUG AND TACK, UP 2" IN A SMALL (6)
QUADRANT APPEARS TO BE ORIGINAL, CLO BT BUT NO POSITIVE IDENTIFICATION WAS FOUND (31)
1984-SEATTLE CITY LIGHT FB SHOWS A FOUND 1-1/2" IRON PIPE WITH S TAG 1985/7 AND A CEAD BT SNAO IN THE NW QUADRANT WITH SCREWS (12)
1988-RECORD OF SURVEY SHOWS A FOUND 1-1/2" IRON PIPE WITH PLUG AND TACK, UP 2" IN A SMALL (6)
2008-RECORD OF SURVEY SHOWS A FOUND 1-1/2" IRON PIPE WITH PLUG AND TACK, UP 2" IN A SMALL (6)
FIELD SEARCH:
- A 14" ALBER BEARS N41°E AT 18.55 FEET TO A STEEL NAIL THAT IS 1.5' UP ON THE NORTHWEST SIDE
- A 14" ALBER BEARS S41°E AT 23.19 FEET TO A STEEL NAIL THAT IS 1.2' UP ON THE NORTHWEST SIDE
- A 14" ALBER BEARS S27°W AT 33.93 FEET TO A STEEL NAIL THAT IS 1.2' UP ON THE NORTHWEST SIDE
- A 4" CEAD STUMP (BT) BEARS N48°W AT 21.18 FEET TO A STEEL NAIL THAT IS 2.0' UP ON THE SOUTHWEST SIDE
- A 20.99 FEET TO A STEEL NAIL THAT IS 1' UP ON THE SOUTHWEST SIDE
SET CASSINITE POST 1' NORTH
FIELDBOOK 7151, PAGE 39

(E09) SECTION CORNER COMMON TO SECTIONS 4, 5, 8, & 9

ACCEPTED IRON PIPE, REPLACED WITH ALUMINUM MONUMENT
HISTORY:
1987-DNR CORNER SHEET SHOWS 4 BRS FOUND BY EMPLOYEE WCD (GONZALEZ/ET/AL) ON 4-18-2022, WE FOUND ONE BRASS DISC IN CONCRETE (MARKED WITH CORNER DESIGNATION AND THE YEAR 1984/14)
FIELD SEARCH:
ON 4-18-2022, WE TIED AND ACCEPTED A 3/4" CONCRETE MONUMENT, 0.4' ABOVE GRADE, WITH A 3/4" DIAMETER DNR BRASS DISC STAMPED WITH CORNER DESIGNATION AND THE YEAR 1984/14. THE MONUMENT AND OLD 2" PIPE IS JAMMED ONTO THE TOP OF THE 1' POST, 18" FR BT STUMP REMAINS, WITH VERGEL (CONCRETE), ONE WH 1.9' TO CENTER.
PERFECTION:
- A 12" CEAD BEARS S40°W AT 10.66 FEET TO A STEEL NAIL THAT IS 2.2' UP ON THE NORTHWEST SIDE
- A 12" HEALDOCK BEARS N27°W AT 33.90 FEET TO A STEEL NAIL THAT IS 2' UP ON THE NORTH SIDE
- A 12" HEALDOCK BEARS N27°W AT 37.70 FEET TO A STEEL NAIL THAT IS 0.6' UP ON THE EAST SIDE
SET CASSINITE POST 1' NORTH
FIELDBOOK 7151, PAGE 25



A SURVEY IN SECTION 5,
TOWNSHIP 33 NORTH, RANGE 10 EAST, WM,
SKAGIT COUNTY

STATE OF WASHINGTON
DEPARTMENT OF NATURAL RESOURCES
LAND SURVEY SECTION - P.O. BOX 47030
OLYMPIA, WASHINGTON 98504-7030 (360) 902-1206

"DOC HOLLIDAY" SURVEY
FIELD CREW: B WILLIAMS, PLS
R THOMAS, L.S.T.
FIELD BOOK: 7151 10/12/2023

FINAL MAP NUMBER: 2245
SHEET 2 OF 2