

CONCRETE SAUK VALLEY ROAD CULVERT REPAIR PROJECT - SOUTH OSTERMAN CREEK

EO214-5

FEDERAL AID NO. 4650DR-WA #674680



SKAGIT COUNTY OFFICIALS

BOARD OF COMMISSIONERS
•LISA JANICKI, CHAIR
•RON WESEN, COMMISSIONER
•PETER BROWNING, COMMISSIONER
PUBLIC WORKS
•MICHAEL SEE, DIRECTOR

APPROVED FOR CONSTRUCTION

THOMAS M. WELLER, P.E. COUNTY ENGINEER DATE

PLAN SHEET INDEX

Table with 2 columns: SHEET, TITLE. Rows include COVER, GENERAL NOTES & ABBREVIATIONS, TESC NOTES & SWPPP ELEMENTS, TEMPORARY TRAFFIC CONTROL PLAN (1 OF 4), TEMPORARY TRAFFIC CONTROL PLAN (2 OF 4), TEMPORARY TRAFFIC CONTROL PLAN (3 OF 4), TEMPORARY TRAFFIC CONTROL PLAN (4 OF 4), TESC PLAN, SITE PREPARATION PLAN, SITE ISOLATION & DEWATERING, SITE ISOLATION & DEWATERING DETAILS, ROAD PLAN & PROFILE, SUPERELEVATION DIAGRAM & TYPICAL SECTIONS, ROAD X-SECTIONS, STRUCTURAL NOTES, CULVERT PLAN & ELEVATION, CULVERT WINGWALL LAYOUTS, CULVERT HEADWALL LAYOUTS, CHANNEL PLAN, CHANNEL PROFILE, TYPICAL CHANNEL SECTIONS, CHANNEL SECTIONS (1 OF 3), CHANNEL SECTIONS (2 OF 3), CHANNEL SECTIONS (3 OF 3), CHANNEL CONSTRUCTION SEQUENCE, CHANNEL STRUCTURE DETAILS (1 OF 3), CHANNEL STRUCTURE DETAILS (2 OF 3), CHANNEL STRUCTURE DETAILS (3 OF 3), PLANTING PLAN, PLANT SCHEDULES & DETAILS.



DAVID EVANS AND ASSOCIATES INC.
1221 Fraser St., Suite E-3
Bellingham, WA, 98229
Phone: 564.565.3100



Natural Systems Design + Coastal Geologic Services





Know what's below
Call before you dig.
Determina lo que está bajo tierra
Llama antes de excavar.

SURVEY NOTES:

HORIZONTAL DATUM: NAD83 WASHINGTON
STATE PLANE NORTH ZONE
VERTICAL DATUM: NAVD88

SUMMARY OF QUANTITIES

Table with 4 columns: ITEM NO., ITEM DESCRIPTION, UNIT, QUANTITY. Rows include MOBILIZATION, MINOR CHANGE, SPCC PLAN, TYPE B PROGRESS SCHEDULE, STRUCTURE SURVEYING, ROADWAY SURVEYING, CHANNEL SURVEYING, PROJECT TEMPORARY TRAFFIC CONTROL, WORK ZONE SAFETY CONTINGENCY, CONSTRUCTION SIGNS CLASS A, PORTABLE CHANGEABLE MESSAGE SIGN, PAINT LINE, FISH EXCLUSION ASSISTANCE, FISH BLOCK NET MAINTENANCE, CLEARING AND GRUBBING, REMOVAL OF STRUCTURES AND OBSTRUCTIONS, SAWCUTTING, ROADWAY EXCAVATION INCL. HAUL, CHANNEL EXCAVATION INCL. HAUL, SLOPE STABILIZATION EXCAVATION INCL. HAUL, SLOPE STABILIZATION FILL, STRUCTURE EXCAVATION CLASS A INCL. HAUL, SHORING OR EXTRA EXCAVATION CL. A, UNSUITABLE FOUNDATION EXCAVATION INCL. HAUL, TEMPORARY DEWATERING SYSTEM, PERMEABLE BALLAST, GRAVEL BORROW INCL. HAUL, CRUSHED SURFACING TOP COURSE, HMA CL. 1/2 IN. PG 58H-22, GRAVEL BACKFILL FOR WALL, PRECAST REINF. CONC. SPLIT BOX CULVERT NO. 1, TEMPORARY STREAM DIVERSION, TIMBER HANDRAIL, EROSION CONTROL AND WATER POLLUTION PREVENTION, STABILIZED CONSTRUCTION ENTRANCE, WATTLE, HIGH VISIBILITY FENCE, SEEDING AND MULCHING, ESC LEAD, PSPIPE VINE MAPLE, 1 GAL, PSPIPE BIGLEAF MAPLE, 1 GAL, PSPIPE COMMON YARROW, 1 GAL, PSPIPE RED ALDER, 1 GAL, PSPIPE KINNIKINNICK, 4", PSPIPE TALL OREGONGRAPE, 1 GAL, PSPIPE REDOSIER DOGWOOD, 1 GAL, PSPIPE BEAKED HAZELNUT, 1 GAL, PSPIPE BLACK HAWTHORN, 1 GAL, PSPIPE OSOBERY, 1 GAL, PSPIPE WESTERN SWORDFERN, 1 GAL, PSPIPE DOUGLAS-FIR, 1 GAL, PSPIPE SPREADING GOOSEBERRY, 1 GAL, PSPIPE THIMBLEBERRY, 1 GAL, PSPIPE SALMONBERRY, 1 GAL, PSPIPE PACIFIC WILLOW, 4' LIVE STAKE, PSPIPE RED ELDERBERRY, 1 GAL, PSPIPE SNOWBERRY, 1 GAL, PSPIPE WESTERN RED CEDAR, 1 GAL, WOOD CHIP MULCH, BEAM GUARDRAIL TYPE 31 - 8 FT. LONG POST, BEAM GUARDRAIL TYPE 31 NON-FLARED TERMINAL, BEAM GUARDRAIL ANCHOR TYPE 11, BOX CULVERT GUARDRAIL STEEL POST TYPE 31, CABLE FENCE, PERMANENT SIGNING, STREAMBED COBBLES 12 IN., STREAMBED SEDIMENT, BOULDER SILL, STREAMBED SAND, INSTREAM WOOD PLACEMENT - LOG TRIANGLE, INSTREAM WOOD PLACEMENT - BANK ROOTWAD, INSTREAM WOOD PLACEMENT - CHANNEL ROOTWAD - SHORT, INSTREAM WOOD PLACEMENT - CHANNEL ROOTWAD - LONG, INSTREAM WOOD PLACEMENT - SLASH WATTLE, CONSTRUCTION GEOTEXTILE FOR SOIL STABILIZATION, STREAMBED BOULDER TYPE 1, STREAMBED BOULDER TYPE 2, STREAMBED BOULDER TYPE 3, STREAMBED BOULDER TYPE 4, RECORD DRAWINGS, APPRENTICESHIP INCENTIVE/PENALTY.



VICINITY MAP NTS

SKAGIT COUNTY PUBLIC WORKS
1800 CONTINENTAL PLACE
MOUNT VERNON, WA 98273-5625
(360) 416-1400
CONCRETE SAUK VALLEY ROAD CULVERT REPAIR PROJECT - SOUTH OSTERMAN CREEK
COVER
1 INCH SCALE BAR
ADJUST SCALE ACCORDINGLY
SHEET 1 OF 30

GENERAL NOTES:

1. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO HAVE A COPY OF THESE APPROVED PLANS PRESENT ON THE CONSTRUCTION SITE AT ALL TIMES.
2. THE CONTRACTOR SHALL ATTEND PRE-CONSTRUCTION CONFERENCE WITH SCPW PRIOR TO BEGINNING CONSTRUCTION.
3. ALL APPROVALS AND PERMITS REQUIRED FOR THE CONSTRUCTION OF THIS PROJECT ARE AVAILABLE AS AN APPENDIX IN THE SPECIAL PROVISIONS, ALSO INCLUDED IS A LIST OF PERMITS THE CONTRACTOR IS RESPONSIBLE FOR PROCURING PRIOR TO CONSTRUCTION
4. ALL WORK SHALL CONFORM TO THE LATEST EDITION OF "STANDARD SPECIFICATIONS FOR ROAD BRIDGE AND MUNICIPAL CONSTRUCTION" CURRENT EDITION (WSDOT) AND THE "SKAGIT COUNTY ROAD STANDARDS" UNLESS INDICATED OTHERWISE BY THE CONTRACT DOCUMENTS. IN CASE OF A CONFLICT BETWEEN THE REGULATORY SPECIFICATIONS OR STANDARDS, THE MORE STRINGENT REQUIREMENT WILL PREVAIL. ALL REFERENCES TO "SPECIFICATION SECTIONS" REFER TO THE MOST CURRENT EDITION OF "STANDARD SPECIFICATIONS FOR ROAD, BRIDGE, AND MUNICIPAL CONSTRUCTION" (WSDOT) UNLESS OTHERWISE NOTED.
5. THIS PROJECT MAY REQUIRE VARIOUS PERMITS AS OUTLINED IN THE PROJECT SPECIFICATION'S GENERAL PROVISIONS. ALL WORK SHALL BE PERFORMED IN A MANNER WHICH ENSURES CONFORMANCE WITH ANY PERMIT REQUIREMENTS.
6. UNDERGROUND UTILITIES ARE KNOWN TO EXIST IN THE AREA OF CONSTRUCTION. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO CONTACT THE UTILITY OWNERS FOR LOCATIONS AND TO NOTIFY THE ENGINEER PROMPTLY OF ANY CONFLICT. THE ONE-CALL NUMBER FOR UNDERGROUND UTILITIES IS: 1-800-424-5555.
7. THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING THE INTEGRITY OF EXISTING UTILITIES AT ALL TIMES WHICH MAY INCLUDE, BUT ARE NOT LIMITED TO, POWER, TELEPHONE, CABLE TV, AND FIBER.
8. THE CONTRACTOR SHALL NOTIFY PROPERTY OWNERS 48 HOURS IN ADVANCE OF ANY WORK AFFECTING ACCESS OR SERVICE AND SHALL MINIMIZE INTERRUPTIONS TO DRIVEWAYS FOR PROPERTY OWNERS ADJACENT TO THE PROJECT.
9. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ALL TRAFFIC CONTROL IN ACCORDANCE WITH THE CURRENT EDITION OF THE MANUAL OF UNIFORM TRAFFIC CONTROL DEVICES (MUTCD) INCLUDING THE WASHINGTON STATE MODIFICATIONS TO THE MUTCD PRIOR TO DISRUPTION OF ANY TRAFFIC. THE CONTRACTOR MAY CHOOSE TO ADOPT THE TRAFFIC CONTROL PLANS PROVIDED IN THIS PLAN SET OR SUBMIT AN ALTERNATIVE TRAFFIC CONTROL PLAN. TRAFFIC CONTROL PLANS MUST BE APPROVED BY SCPW AND WSDOT FOR APPROVAL, THIS APPROVAL TAKES TIME AND NO WORK SHALL COMMENCE UNTIL PLANS ARE APPROVED AND ALL APPROVED TRAFFIC CONTROL IS IN PLACE.
10. PUBLIC RIGHTS-OF-WAY SHALL BE KEPT IN A CLEAN AND SERVICEABLE CONDITION AT ALL TIMES. IN THE EVENT MATERIALS ARE INADVERTENTLY DEPOSITED ON ROADWAYS, THE MATERIAL SHALL BE PROMPTLY REMOVED.
11. ALL LAWN AND VEGETATED AREAS OUTSIDE THE PROJECT LIMITS DISTURBED BY CONSTRUCTION EQUIPMENT, VEHICLES OR PERSONNEL SHALL BE RESTORED TO ORIGINAL CONDITION OR BETTER, AT THE CONTRACTOR'S EXPENSE.

CONSTRUCTION SWPPP NOTES:

1. APPROVAL OF THIS EROSION/SEDIMENTATION PLAN (SWPPP) SHALL BE PREPARED BY THE CONTRACTOR IN COMPLIANCE WITH THE DOE STORMWATER MANAGEMENT MANUAL FOR WESTERN WASHINGTON ADDRESSING, AND THE WESTERN WASHINGTON HYDROLOGY MANUAL ADDRESSING ALL APPLICABLE MINIMUM REQUIREMENTS. THE AREAS OF NEW AND/OR REPLACED IMPERVIOUS SURFACE SHALL BE INCLUDED IN THE SWPPP. THE CONTRACTOR SHALL SUBMIT THE SWPPP FOR THE ENGINEER'S APPROVAL BEFORE ANY WORK BEGINS IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS.
2. THE IMPLEMENTATION OF THIS TESC PLAN AND THE CONSTRUCTION, MAINTENANCE, REPLACEMENT, AND UPGRADING OF THESE TESC BMPS IS THE RESPONSIBILITY OF THE PERMIT HOLDER UNTIL ALL CONSTRUCTION IS COMPLETED AND APPROVED AND VEGETATION/LANDSCAPING IS ESTABLISHED.
3. CONTRACTOR SHALL CLEARLY FLAG THE BOUNDARIES OF THE CLEARING LIMITS SHOWN ON THIS PLAN IN THE FIELD PRIOR TO CONSTRUCTION. DURING THE CONSTRUCTION PERIOD, NO DISTURBANCE BEYOND THE FLAGGED CLEARING LIMITS SHALL BE PERMITTED. THE FLAGGING SHALL BE MAINTAINED BY THE CONTRACTOR FOR THE DURATION OF CONSTRUCTION.
4. CONSTRUCT THE TESC BMPS SHOWN ON THIS PLAN IN CONJUNCTION WITH ALL CLEARING AND GRADING ACTIVITIES, AND IN SUCH A MANNER AS TO ENSURE THAT SEDIMENT AND SEDIMENT LADEN WATER DO NOT ENTER THE DRAINAGE SYSTEM, ROADWAYS, OR VIOLATE APPLICABLE WATER STANDARDS.
5. THE TESC BMPS SHOWN ON THIS PLAN ARE THE MINIMUM REQUIREMENTS FOR ANTICIPATED SITE CONDITIONS. DURING THE CONSTRUCTION PERIOD, UPGRADE THESE ESC BMPS AS NEEDED FOR UNEXPECTED STORM EVENTS AND TO ENSURE THAT SEDIMENT AND SEDIMENT-LADEN WATER DO NOT LEAVE THE SITE.
6. THE PERMIT HOLDER SHALL INSPECT THE ESC BMPS DAILY AND MAINTAIN THEM AS NECESSARY TO ENSURE THEIR CONTINUED FUNCTIONING.
7. INSPECT AND MAINTAIN THE TESC BMPS ON INACTIVE SITES A MINIMUM OF ONCE A MONTH OR WITHIN THE 48 HOURS FOLLOWING A MAJOR STORM EVENT (I.E. A 24-HOUR STORM EVENT WITH A 10-YR OR GREATER RECURRENCE INTERVAL).
8. AT NO TIME SHALL THE SEDIMENT EXCEED 60-PERCENT OF THE SUMP DEPTH OR HAVE LESS THAN 6-INCHES OF CLEARANCE FROM THE SEDIMENT SURFACE TO THE INVERT OF THE LOWEST PIPE. ALL CATCH BASINS AND CONVEYANCE LINES SHALL BE CLEANED PRIOR TO PAVING. THE CLEANING OPERATION SHALL NOT FLUSH SEDIMENT LADEN WATER INTO THE DOWNSTREAM SYSTEM.
9. INSTALL STABILIZED CONSTRUCTION ENTRANCES AT THE BEGINNING OF CONSTRUCTION AND MAINTAIN FOR THE DURATION OF THE PROJECT. ADDITIONAL MEASURES MAY BE REQUIRED TO ENSURE THAT ALL PAVED AREAS ARE KEPT CLEAN FOR THE DURATION OF THE PROJECT.

ENVIRONMENTAL NOTES:

1. A STORMWATER POLLUTION PREVENTION PLAN (SWPPP) SHALL BE PREPARED BY THE CONTRACTOR IN COMPLIANCE WITH THE DOE STORMWATER MANAGEMENT MANUAL FOR WESTERN WASHINGTON ADDRESSING, AND THE WESTERN WASHINGTON HYDROLOGY MANUAL ADDRESSING ALL APPLICABLE MINIMUM REQUIREMENTS. THE AREAS OF NEW AND/OR REPLACED IMPERVIOUS SURFACE SHALL BE INCLUDED IN THE SWPPP. THE CONTRACTOR SHALL SUBMIT THE SWPPP FOR THE ENGINEER'S APPROVAL BEFORE ANY WORK BEGINS IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS.
2. THE CONTRACTOR SHALL PREPARE A SPILL PREVENTION, CONTROL AND COUNTER MEASURES (SPCC) PLAN THAT SATISFIES THE CURRENT WSDOT SPECIFICATION 1-07.15 (1) AND THE NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM (NPDES) REQUIREMENTS. THE PLAN WILL BE REVIEWED AND APPROVED PRIOR TO COMMENCEMENT OF WORK.
3. THE CONTRACTOR SHALL BE RESPONSIBLE FOR CONSTRUCTING, MAINTAINING, & REMOVING EROSION CONTROL MEASURES (SILT FENCE, ROCK CHECK DAMS, SILT PONDS, CATCH BASIN FILTERS, ETC.) THROUGHOUT THE DURATION OF THE PROJECT. ALL REMOVAL OF EROSION CONTROL WORK IS CONSIDERED INCIDENTAL TO THE ITEMS OF WORK IN THE CONTRACT FOR THIS PROJECT. REFER TO THE "STORM WATER POLLUTION PREVENTION PLAN AND BID ITEMS NOTED IN THE CONTRACT PORTION OF THE PROJECT SPECIFICATIONS FOR SPECIFIC EROSION CONTROL NOTES.

ABBREVIATIONS

ABT ALUM AP ACZA	ABOUT ALUMINUM ANGLE POINT AMMONIACAL COPPER ZINC ARSENATE	EVCE EVCS EX, EXIST	END VERTICAL CURVE ELEVATION END VERTICAL CURVE STATION EXISTING	OD OFF OHWM OPP	OUTSIDE DIAMETER ORANGE FLEXIBLE FENCING ORDINARY HIGH WATER MARK OPPOSITE	SPCC SPL SQ ST STA STD	SPILL PREVENTION CONTROL COUNTERMEASURES SPLICE SQUARE STREET STATION STANDARD
BK BMP BRG BTWN BVCE	BACK BEST MANAGEMENT PRACTICE BEARING BETWEEN BEGIN VERTICAL CURVE ELEVATION BEGIN VERTICAL CURVE STATION	FDN FF FIN FND	FOUNDATION FINISHED FLOOR FINISH FOUND	PC PCC POB POC POC PCF PK PNT PRC PSI PT PVC PVMT	POINT OF CURVATURE PORTLAND CONCRETE CEMENT POINT OF BEGINNING POINT ON CURVE POINT OF ENDING POUNDS PER CUBIC FOOT PARKER-KALON POINT POINT OF REVERSE CURVE POUNDS PER SQUARE INCH POINT OF TANGENT POLYVINYL CHLORIDE PAVEMENT	SWPPP SY SYMM	STORMWATER POLLUTION PREVENTION PLAN SQUARE YARD SYMMETRICAL
CL C/L CLR CMP CONC CONST CSTC	CLASS CENTERLINE CLEAR, CLEARANCE CORRUGATED METAL PIPE CONCRETE CONSTRUCTION CRUSHED SURFACING TOP COURSE CONSTRUCTION STORMWATER GENERAL PERMIT CUBIC YARD	IE IN INT	INVERT ELEVATION INCH INTERIOR	HMA JT	HOT MIX ASPHALT JOINT	TCE TEMP TYP	TEMPORARY CONSTRUCTION EASEMENT TEMPORARY TYPICAL
DIAM, Ø DIP DWG DWL DIAPH	DIAMETER DUCTILE IRON PIPE DRAWING DOWEL DIAPHRAGM	LB LF LONGIT LS LT	POUND LINEAR FEET LOGITUDINAL LUMP SUM, LOW SHRINKAGE LEFT	R RDWY RE REF REINF REQD RP RR RT R/W	RADIUS ROADWAY RIM ELEVATION REFERENCE REINFORCING REQUIRED RADIUS POINT RAILROAD RIGHT RIGHT OF WAY	USPS W/ WSDOT	UNITED STATES POSTAL SERVICE WITH WASHINGTON STATE DEPARTMENT OF TRANSPORTATION
E EA EG EL, ELEV ESC	EASTING EACH EXISTING GROUND ELEVATION EROSION & SEDIMENT CONTROL	NO NPDES	NUMBER NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM NOT TO SCALE	SCHED SCPW SF SHLD SHT SIM SSK HD SLP SPA	SCHEDULE SKAGIT COUNTY PUBLIC WORKS SQUARE FEET SHOULDER SHEET SIMILAR COUNTERSUNK HEAD SLOPE SPACE	X- YR	CROSS YEAR

CONCRETE SAUK VALLEY ROAD ALIGNMENT TABLE

NO.	RADIUS	LENGTH	LINE/CHORD BEARING	DELTA	START STATION	END STATION	START COORDINATE	END COORDINATE
C1	190.00'	151.97'	N33°48'28"W	45°49'35"	100+00.00	101+51.97	N=526,242.9 E=1,454,214.5	N=526,365.8E=1,454,132.1
L1		248.03'	N12°16'16"W		101+51.97	104+00.00	N=526,365.8 E=1,454,132.1	N=526,608.2 E=1,454,079.4

S. OSTERMAN CREEK DESIGN ALIGNMENT TABLE (CONT.)

NO.	RADIUS	LENGTH	LINE/CHORD BEARING	DELTA	START STATION	END STATION	START COORDINATE	END COORDINATE
L7		1.20'	N35°12'42"E		217+38.87	217+37.68	N=526,448.7 E=1,454,206.0	N=526,449.7 E=1,454,206.7
C7	50.00'	69.82'	N75°12'53"E	80°00'21"	217+37.68	216+67.86	N=526,449.7 E=1,454,206.7	N=526,466.1E=1,454,268.9
L8		19.69'	S64°46'57"E		216+67.86	216+48.17	N=526,466.1 E=1,454,268.9	N=526,457.7 E=1,454,286.7
C8	61.07'	52.53'	S40°08'18"E	49°17'18"	216+48.17	215+95.63	N=526,457.7 E=1,454,286.7	N=526,418.8E=1,454,319.5
L9		3.43'	S15°29'39"E		215+95.63	215+92.20	N=526,418.8 E=1,454,319.5	N=526,415.5 E=1,454,320.4
C9	29.76'	33.69'	S47°55'26"E	64°51'33"	215+92.20	215+58.51	N=526,415.5 E=1,454,320.4	N=526,394.1E=1,454,344.1
L10		1.85'	S80°21'12"E		215+58.51	215+56.66	N=526,394.1 E=1,454,344.1	N=526,393.8 E=1,454,345.9
C10	20.00'	20.06'	N70°54'40"E	57°28'16"	215+56.66	215+36.60	N=526,393.8 E=1,454,345.9	N=526,400.0E=1,454,364.1
L11		46.71'	N42°10'32"E		215+36.60	214+89.89	N=526,400.0 E=1,454,364.1	N=526,434.7 E=1,454,395.5



DAVID EVANS
AND ASSOCIATES INC.

PROJECT NO.: EO214-S
FED. AID NO.: 4850DRWA #674680
DESIGNED BY: R.S.B.
CHECKED BY: R.S.B.
DRAWN BY: R.S.B.
APPROVED BY: R.W.
PROJECT LOCATED NEAR:
CONCRETE, WA
S 14 T 34 N R 9 E

CONCRETE SAUK VALLEY ROAD
CULVERT REPAIR PROJECT -
SOUTH OSTERMAN CREEK
GENERAL NOTES & ABBREVIATIONS

1 INCH SCALE BAR
ADJUST SCALE ACCORDINGLY
SHEET
2 OF 30

DESIGN ENGINEER
ENGINEER OF RECORD
NO. 9-29-25

Skagit County
Public Works
1800 CONTINENTAL PLACE
MOUNT VERNON, WA 98273-5625
(360) 416-1400

CONSTRUCTION STORMWATER POLLUTION PREVENTION (SWPPP) ELEMENTS:

ELEMENT 1 – PRESERVE VEGETATION/MARK CLEARING LIMITS

- a. BEFORE BEGINNING LAND-DISTURBING ACTIVITIES, INCLUDING CLEARING AND GRADING, CLEARLY MARK ALL CLEARING LIMITS, SENSITIVE AREAS AND THEIR BUFFERS, AND TREES THAT ARE TO BE PRESERVED WITHIN THE CONSTRUCTION AREA.
- b. RETAIN THE DUFF LAYER, NATIVE TOPSOIL, AND NATURAL VEGETATION IN AN UNDISTURBED STATE TO THE MAXIMUM DEGREE PRACTICABLE.

ELEMENT 2 – ESTABLISH CONSTRUCTION ACCESS

- a. LIMIT CONSTRUCTION VEHICLE ACCESS AND EXIT TO ONE ROUTE, IF POSSIBLE.
- b. STABILIZE ACCESS POINTS WITH A PAD OF QUARRY SPALLS, CRUSHED ROCK, OR OTHER EQUIVALENT BMPS, TO MINIMIZE TRACKING SEDIMENT ONTO PUBLIC ROADS.
- c. LOCATE WHEEL WASH OR TIRE BATHS ON SITE, IF THE STABILIZED CONSTRUCTION ENTRANCE IS NOT EFFECTIVE IN PREVENTING TRACKING SEDIMENT ONTO PUBLIC ROADS.
- d. IF SEDIMENT IS TRACKED OFF SITE, CLEAN THE AFFECTED ROADWAY THOROUGHLY AT THE END OF EACH DAY, OR MORE FREQUENTLY AS NECESSARY (FOR EXAMPLE, DURING WET WEATHER). REMOVE SEDIMENT FROM ROADS BY SHOVELING, SWEEPING, OR PICKUP AND TRANSPORT OF THE SEDIMENT TO A CONTROLLED SEDIMENT DISPOSAL AREA.
- e. CONDUCT STREET WASHING ONLY AFTER SEDIMENT REMOVAL IN ACCORDANCE WITH 2.d ABOVE.
- f. CONTROL STREET WASH WASTEWATER BY PUMPING BACK ON SITE OR OTHERWISE PREVENTING IT FROM DISCHARGING INTO SYSTEMS TRIBUTARY TO WATERS OF THE STATE.

ELEMENT 3 – CONTROL FLOW RATES

- a. PROTECT PROPERTIES AND WATERWAYS DOWNSTREAM OF DEVELOPMENT SITES FROM EROSION AND THE ASSOCIATED DISCHARGE OF TURBID WATERS DUE TO INCREASES IN THE VELOCITY AND PEAK VOLUMETRIC FLOW RATE OF STORMWATER RUNOFF FROM THE PROJECT SITE, AS REQUIRED BY LOCAL PLAN APPROVAL AUTHORITY.
- b. WHERE NECESSARY TO COMPLY WITH 3.a (ABOVE), CONSTRUCT STORMWATER INFILTRATION OR DETENTION BMPS AS ONE OF THE FIRST STEPS IN GRADING. ASSURE THAT DETENTION BMPs FUNCTION PROPERLY BEFORE CONSTRUCTING SITE IMPROVEMENTS (E.G., IMPERVIOUS SURFACES).
- c. IF PERMANENT INFILTRATION PONDS ARE USED FOR FLOW CONTROL DURING CONSTRUCTION, PROTECT THESE FACILITIES FROM SILTATION DURING THE CONSTRUCTION PHASE.

ELEMENT 4 – INSTALL SEDIMENT CONTROLS

THE PERMITTEE MUST DESIGN, INSTALL AND MAINTAIN EFFECTIVE EROSION CONTROLS AND SEDIMENT CONTROLS TO MINIMIZE THE DISCHARGE OF POLLUTANTS. AT A MINIMUM, THE PERMITTEE MUST DESIGN, INSTALL AND MAINTAIN SUCH CONTROLS TO:

- a. CONSTRUCT SEDIMENT CONTROL BMPS (SEDIMENT PONDS, TRAPS, FILTERS, INFILTRATION FACILITIES, ETC.) AS ONE OF THE FIRST STEPS IN GRADING. THESE BMPS MUST BE FUNCTIONAL BEFORE OTHER LAND DISTURBING ACTIVITIES TAKE PLACE.
- b. MINIMIZE SEDIMENT DISCHARGES FROM THE SITE. THE DESIGN, INSTALLATION, AND MAINTENANCE OF EROSION AND SEDIMENT CONTROLS MUST ADDRESS FACTORS SUCH AS THE AMOUNT, FREQUENCY, INTENSITY AND DURATION OF PRECIPITATION; THE NATURE OF RESULTING STORMWATER RUNOFF; AND SOIL CHARACTERISTICS, INCLUDING THE RANGE OF SOIL PARTICLE SIZES EXPECTED TO BE PRESENT ON THE SITE.
- c. DIRECT STORMWATER RUNOFF FROM DISTURBED AREAS THROUGH A SEDIMENT POND OR OTHER APPROPRIATE SEDIMENT REMOVAL BMP BEFORE THE RUNOFF LEAVES A CONSTRUCTION SITE OR BEFORE DISCHARGE TO AN INFILTRATION FACILITY. RUNOFF FROM FULLY STABILIZED AREAS MAY BE DISCHARGED WITHOUT A SEDIMENT REMOVAL BMP BUT MUST CONTROL FLOW RATES PER ELEMENT 3: CONTROL FLOW RATES.
- d. LOCATE BMPS INTENDED TO TRAP SEDIMENT ON SITE IN A MANNER TO AVOID INTERFERENCE WITH THE MOVEMENT OF JUVENILE SALMONIDS ATTEMPTING TO ENTER OFF-CHANNEL AREAS OR DRAINAGES.
- e. PROVIDE AND MAINTAIN NATURAL BUFFERS AROUND SURFACE WATERS. DIRECT STORMWATER TO VEGETATED AREAS TO INCREASE SEDIMENT REMOVAL AND MAXIMIZE STORMWATER INFILTRATION, UNLESS INFEASIBLE.
- f. WHERE FEASIBLE, DESIGN OUTLET STRUCTURES THAT WITHDRAW IMPOUNDED STORMWATER FROM THE SURFACE TO AVOID DISCHARGING SEDIMENT THAT IS STILL SUSPENDED LOWER IN THE WATER COLUMN.

ELEMENT 5 – STABILIZE SOILS

- a. THE PERMITTEE MUST STABILIZE EXPOSED AND UNWORKED SOILS BY APPLICATION OF EFFECTIVE BMPS THAT PREVENT EROSION. APPLICABLE BMPS INCLUDE BUT ARE NOT LIMITED TO: TEMPORARY AND PERMANENT SEEDING, SODDING, MULCHING, PLASTIC COVERING, EROSION CONTROL FABRICS AND MATTING, SOIL APPLICATION OF POLYACRYLAMIDE (PAM), THE EARLY APPLICATION OF GRAVEL BASE ON AREAS TO BE PAVED, AND DUST CONTROL.
- b. THE PERMITTEE MUST CONTROL STORMWATER VOLUME AND VELOCITY WITHIN THE SITE TO MINIMIZE SOIL EROSION.
- c. THE PERMITTEE MUST CONTROL STORMWATER DISCHARGES, INCLUDING BOTH PEAK FLOW RATES AND TOTAL STORMWATER VOLUME, TO MINIMIZE EROSION AT OUTLETS AND TO MINIMIZE DOWNSTREAM CHANNEL AND STREAM BANK EROSION.
- d. DEPENDING ON THE GEOGRAPHIC LOCATION OF THE PROJECT, THE PERMITTEE MUST NOT ALLOW SOILS TO REMAIN EXPOSED AND UNWORKED FOR MORE THAN THE TIME PERIODS SET FORTH BELOW TO PREVENT EROSION:
- WEST OF THE CASCADE MOUNTAINS CREST
DURING THE DRY SEASON (MAY 1 – SEPTEMBER 30): 7 DAYS DURING THE WET SEASON (OCTOBER 1 – APRIL 30): 2 DAYS
- EAST OF THE CASCADE MOUNTAINS CREST, EXCEPT FOR CENTRAL BASIN* DURING THE DRY SEASON (JULY 1 – SEPTEMBER 30): 10 DAYS
DURING THE WET SEASON (OCTOBER 1 – JUNE 30): 5 DAYS
- THE CENTRAL BASIN*, EAST OF THE CASCADE MOUNTAINS CREST DURING THE DRY SEASON (JULY 1 – SEPTEMBER 30): 30 DAYS DURING THE WET SEASON (OCTOBER 1 – JUNE 30): 15 DAYS **NOTE** THE CENTRAL BASIN IS DEFINED AS THE PORTIONS OF EASTERN WASHINGTON WITH MEAN ANNUAL PRECIPITATION OF FEWER THAN 12 INCHES.
- e. THE PERMITTEE MUST STABILIZE SOILS AT THE END OF THE SHIFT BEFORE A HOLIDAY OR WEEKEND IF NEEDED BASED ON THE WEATHER FORECAST.
- f. THE PERMITTEE MUST STABILIZE SOIL STOCKPILES FROM EROSION, PROTECTED WITH SEDIMENT TRAPPING MEASURES, AND WHERE POSSIBLE, BE LOCATED AWAY FROM STORM DRAIN INLETS, WATERWAYS, AND DRAINAGE CHANNELS.
- g. THE PERMITTEE MUST MINIMIZE THE AMOUNT OF SOIL EXPOSED DURING CONSTRUCTION ACTIVITY.
- h. THE PERMITTEE MUST MINIMIZE THE DISTURBANCE OF STEEP SLOPES.
- i. THE PERMITTEE MUST MINIMIZE SOIL COMPACTION AND, UNLESS INFEASIBLE, PRESERVE TOPSOIL.

ELEMENT 6 – PROTECT SLOPES

- a. THE PERMITTEE MUST DESIGN AND CONSTRUCT CUT-AND-FILL SLOPES IN A MANNER TO MINIMIZE EROSION. APPLICABLE PRACTICES INCLUDE, BUT ARE NOT LIMITED TO, REDUCING CONTINUOUS LENGTH OF SLOPE WITH TERRACING AND DIVERSIONS, REDUCING SLOPE STEEPNESS, AND ROUGHENING SLOPE SURFACES (FOR EXAMPLE, TRACK WALKING).
- b. THE PERMITTEE MUST DIVERT OFF-SITE STORMWATER (RUN-ON) OR GROUNDWATER AWAY FROM SLOPES AND DISTURBED AREAS WITH INTERCEPTOR DIKES, PIPES, AND/OR SWALES. OFF-SITE STORMWATER SHOULD BE MANAGED SEPARATELY FROM STORMWATER GENERATED ON THE SITE.
- c. AT THE TOP OF SLOPES, COLLECT DRAINAGE IN PIPE SLOPE DRAINS OR PROTECTED CHANNELS TO PREVENT EROSION.
- i. WEST OF THE CASCADE MOUNTAINS CREST: TEMPORARY PIPE SLOPE DRAINS MUST HANDLE THE PEAK 10-MINUTE FLOW RATE FROM A TYPE 1A, 10-YEAR, 24-HOUR FREQUENCY STORM FOR THE DEVELOPED CONDITION. ALTERNATIVELY, THE 10-YEAR, 1-HOUR FLOW RATE PREDICTED BY AN APPROVED CONTINUOUS RUNOFF MODEL, INCREASED BY A FACTOR OF 1.6, MAY BE USED. THE HYDROLOGIC ANALYSIS MUST USE THE EXISTING LAND COVER CONDITION FOR PREDICTING FLOW RATES FROM TRIBUTARY AREAS OUTSIDE THE PROJECT LIMITS. FOR TRIBUTARY AREAS ON THE PROJECT SITE, THE ANALYSIS MUST USE THE TEMPORARY OR PERMANENT PROJECT LAND COVER CONDITION, WHICHEVER WILL PRODUCE THE HIGHEST FLOW RATES. IF USING THE WESTERN WASHINGTON HYDROLOGY MODEL (WWHM) TO PREDICT FLOWS, BARE SOIL AREAS SHOULD BE MODELED AS "LANDSCAPED AREA."
- ii. EAST OF THE CASCADE MOUNTAINS CREST: TEMPORARY PIPE SLOPE DRAINS MUST HANDLE THE EXPECTED PEAK FLOW RATE FROM A 6-MONTH, 3-HOUR STORM FOR THE DEVELOPED CONDITION, REFERRED TO AS THE SHORT DURATION STORM.

- i. PLACE EXCAVATED MATERIAL ON THE UPHILL SIDE OF TRENCHES, CONSISTENT WITH SAFETY AND SPACE CONSIDERATIONS.

- j. PLACE CHECK DAMS AT REGULAR INTERVALS WITHIN CONSTRUCTED CHANNELS THAT ARE CUT DOWN A SLOPE.

ELEMENT 7 – PROTECT DRAIN INLETS

- a. PROTECT ALL STORM DRAIN INLETS MADE OPERABLE DURING CONSTRUCTION SO THAT STORMWATER RUNOFF DOES NOT ENTER THE CONVEYANCE SYSTEM WITHOUT FIRST BEING FILTERED OR TREATED TO REMOVE SEDIMENT.
- b. CLEAN OR REMOVE AND REPLACE INLET PROTECTION DEVICES WHEN SEDIMENT HAS FILLED ONE-THIRD OF THE AVAILABLE STORAGE (UNLESS A DIFFERENT STANDARD IS SPECIFIED BY THE PRODUCT MANUFACTURER).

ELEMENT 8 – STABILIZE CHANNELS AND OUTLETS

- a. DESIGN, CONSTRUCT, AND STABILIZE ALL ON-SITE CONVEYANCE CHANNELS TO PREVENT EROSION FROM THE FOLLOWING EXPECTED PEAK FLOWS:
- i. WEST OF THE CASCADE MOUNTAINS CREST: CHANNELS MUST HANDLE THE PEAK 10-MINUTE FLOW RATE FROM A TYPE 1A, 10-YEAR, 24-HOUR FREQUENCY STORM FOR THE DEVELOPED CONDITION. ALTERNATIVELY, THE 10-YEAR, 1-HOUR FLOW RATE INDICATED BY AN APPROVED CONTINUOUS RUNOFF MODEL, INCREASED BY A FACTOR OF 1.6, MAY BE USED. THE HYDROLOGIC ANALYSIS MUST USE THE EXISTING LAND COVER CONDITION FOR PREDICTING FLOW RATES FROM TRIBUTARY AREAS OUTSIDE THE PROJECT LIMITS. FOR TRIBUTARY AREAS ON THE PROJECT SITE, THE ANALYSIS MUST USE THE TEMPORARY OR PERMANENT PROJECT LAND COVER CONDITION, WHICHEVER WILL PRODUCE THE HIGHEST FLOW RATES. IF USING THE WWHM TO PREDICT FLOWS, BARE SOIL AREAS SHOULD BE MODELED AS "LANDSCAPED AREA."
- ii. EAST OF THE CASCADE MOUNTAINS CREST: CHANNELS MUST HANDLE THE EXPECTED PEAK FLOW RATE FROM A 6-MONTH, 3-HOUR STORM FOR THE DEVELOPED CONDITION, REFERRED TO AS THE SHORT DURATION STORM.

- b. PROVIDE STABILIZATION, INCLUDING ARMORING MATERIAL, ADEQUATE TO PREVENT EROSION OF OUTLETS, ADJACENT STREAM BANKS, SLOPES, AND DOWNSTREAM REACHES AT THE OUTLETS OF ALL CONVEYANCE SYSTEMS.

ELEMENT 9 – CONTROL POLLUTANTS

DESIGN, INSTALL, IMPLEMENT, AND MAINTAIN EFFECTIVE POLLUTION PREVENTION MEASURES TO MINIMIZE THE DISCHARGE OF POLLUTANTS. THE PERMITTEE MUST:

- a. HANDLE AND DISPOSE OF ALL POLLUTANTS, INCLUDING WASTE MATERIALS AND DEMOLITION DEBRIS THAT OCCUR ON SITE IN A MANNER THAT DOES NOT CAUSE CONTAMINATION OF STORMWATER.
- b. PROVIDE COVER, CONTAINMENT, AND PROTECTION FROM VANDALISM FOR ALL CHEMICALS, LIQUID PRODUCTS, PETROLEUM PRODUCTS, AND OTHER MATERIALS THAT HAVE THE POTENTIAL TO POSE A THREAT TO HUMAN HEALTH OR THE ENVIRONMENT. ON-SITE FUELING TANKS MUST INCLUDE SECONDARY CONTAINMENT. SECONDARY CONTAINMENT MEANS PLACING TANKS OR CONTAINERS WITHIN AN IMPERVIOUS STRUCTURE CAPABLE OF CONTAINING 110% OF THE VOLUME CONTAINED IN THE LARGEST TANK WITHIN THE CONTAINMENT STRUCTURE. DOUBLE-WALLED TANKS DO NOT REQUIRE ADDITIONAL SECONDARY CONTAINMENT.
- c. CONDUCT MAINTENANCE, FUELING, AND REPAIR OF HEAVY EQUIPMENT AND VEHICLES USING SPILL PREVENTION AND CONTROL MEASURES. CLEAN CONTAMINATED SURFACES IMMEDIATELY FOLLOWING ANY SPILL INCIDENT.
- d. DISCHARGE WHEEL WASH OR TIRE BATH WASTEWATER TO A SEPARATE ON-SITE TREATMENT SYSTEM THAT PREVENTS DISCHARGE TO SURFACE WATER, SUCH AS CLOSED-LOOP RECIRCULATION OR UPLAND LAND APPLICATION, OR TO THE SANITARY SEWER WITH LOCAL SEWER DISTRICT APPROVAL.
- e. APPLY FERTILIZERS AND PESTICIDES IN A MANNER AND AT APPLICATION RATES THAT WILL NOT RESULT IN LOSS OF CHEMICAL TO STORMWATER RUNOFF. FOLLOW MANUFACTURERS' LABEL REQUIREMENTS FOR APPLICATION RATES AND PROCEDURES.
- f. USE BMPS TO PREVENT CONTAMINATION OF STORMWATER RUNOFF BY pH-MODIFYING SOURCES. THE SOURCES FOR THIS CONTAMINATION INCLUDE, BUT ARE NOT LIMITED TO: BULK CEMENT, CEMENT KILN DUST, FLY ASH, NEW CONCRETE WASHING AND CURING WATERS, RECYCLED CONCRETE STOCKPILES, WASTE STREAMS GENERATED FROM CONCRETE GRINDING AND SAWING, EXPOSED AGGREGATE PROCESSES, DEWATERING CONCRETE VAULTS, CONCRETE PUMPING, AND MIXER WASHOUT WATERS.
- g. ADJUST THE pH OF STORMWATER OR AUTHORIZED NON-STORMWATER IF NECESSARY TO PREVENT AN EXCEEDANCE OF GROUNDWATER AND/OR SURFACE WATER QUALITY STANDARDS.
- h. ASSURE THAT WASHOUT OF CONCRETE TRUCKS IS PERFORMED OFF-SITE OR IN DESIGNATED CONCRETE WASHOUT AREAS ONLY. DO NOT WASH OUT CONCRETE TRUCK DRUMS OR CONCRETE HANDLING EQUIPMENT ONTO THE GROUND, OR INTO STORM DRAINS, OPEN DITCHES, STREETS, OR STREAMS. WASHOUT OF CONCRETE HANDLING EQUIPMENT MAY BE DISPOSED OF IN A DESIGNATED CONCRETE WASHOUT AREA OR IN A FORMED AREA AWAITING CONCRETE WHERE IT WILL NOT CONTAMINATE SURFACE OR GROUNDWATER. DO NOT DUMP EXCESS CONCRETE ON SITE, EXCEPT IN DESIGNATED CONCRETE WASHOUT AREAS. CONCRETE SPILLAGE OR CONCRETE DISCHARGE DIRECTLY TO GROUNDWATER OR SURFACE WATERS OF THE STATE IS PROHIBITED. DO NOT WASH OUT TO FORMED AREAS AWAITING LID FACILITIES.
- i. OBTAIN WRITTEN APPROVAL FROM ECOLOGY BEFORE USING ANY CHEMICAL TREATMENT, EXCEPT FOR CO2, DRY ICE, OR FOOD GRADE VINEGAR TO ADJUST pH.

- j. UNCONTAMINATED WATER FROM WATER-ONLY BASED SHAFT DRILLING FOR CONSTRUCTION OF BUILDING, ROAD, AND BRIDGE FOUNDATIONS MAY BE INFILTRATED PROVIDED THE WASTEWATER IS MANAGED IN A WAY THAT PROHIBITS DISCHARGE TO SURFACE WATERS. PRIOR TO INFILTRATION, WATER FROM WATER-ONLY BASED SHAFT DRILLING THAT COMES INTO CONTACT WITH CURING CONCRETE MUST BE NEUTRALIZED UNTIL pH IS IN THE RANGE OF 6.5 TO 8.5 (SU).

ELEMENT 10 – CONTROL DEWATERING

- a. PERMITTEES MUST DISCHARGE FOUNDATION, VAULT, AND TRENCH DEWATERING WATER, WHICH HAVE CHARACTERISTICS SIMILAR TO STORMWATER RUNOFF AT THE SITE, INTO A CONTROLLED CONVEYANCE SYSTEM BEFORE DISCHARGE TO A SEDIMENT TRAP OR SEDIMENT POND.
- b. PERMITTEES MAY DISCHARGE CLEAN, NON-TURBID DEWATERING WATER, SUCH AS WELL-POINT GROUNDWATER, TO SYSTEMS TRIBUTARY TO, OR DIRECTLY INTO SURFACE WATERS OF THE STATE, AS SPECIFIED IN ELEMENT 8: STABILIZE CHANNELS AND OUTLETS, PROVIDED THE DEWATERING FLOW DOES NOT CAUSE EROSION OR FLOODING OF RECEIVING WATERS, DO NOT ROUTE CLEAN DEWATERING WATER THROUGH STORMWATER SEDIMENT PONDS, NOTE THAT "SURFACE WATERS OF THE STATE" MAY EXIST ON A CONSTRUCTION SITE AS WELL AS OFF SITE; FOR EXAMPLE, A CREEK RUNNING THROUGH A SITE.
- c. OTHER DEWATERING TREATMENT OR DISPOSAL OPTIONS MAY INCLUDE:
- i. INFILTRATION
- ii. TRANSPORT OFF SITE IN A VEHICLE, SUCH AS A VACUUM FLUSH TRUCK, FOR LEGAL DISPOSAL IN A MANNER THAT DOES NOT POLLUTE STATE WATERS.
- iii. ECOLOGY-APPROVED ON-SITE CHEMICAL TREATMENT OR OTHER SUITABLE TREATMENT TECHNOLOGIES.
- iv. SANITARY OR COMBINED SEWER DISCHARGE WITH LOCAL SEWER DISTRICT APPROVAL, IF THERE IS NO OTHER OPTION.
- v. USE OF A SEDIMENTATION BAG WITH DISCHARGE TO A DITCH OR SWALE FOR SMALL VOLUMES OF LOCALIZED DEWATERING.
- vi. PERMITTEES MUST HANDLE HIGHLY TURBID OR CONTAMINATED DEWATERING WATER SEPARATELY FROM STORMWATER.

ELEMENT 11 – MAINTAIN BMPS

- a. PERMITTEES MUST MAINTAIN AND REPAIR ALL TEMPORARY AND PERMANENT EROSION AND SEDIMENT CONTROL BMPS AS NEEDED TO ASSURE CONTINUED PERFORMANCE OF THEIR INTENDED FUNCTION IN ACCORDANCE WITH BMP SPECIFICATIONS.
- b. PERMITTEES MUST REMOVE ALL TEMPORARY EROSION AND SEDIMENT CONTROL BMPS WITHIN 30 DAYS AFTER ACHIEVING FINAL SITE STABILIZATION OR AFTER THE TEMPORARY BMPS ARE NO LONGER NEEDED.

ELEMENT 12 – MANAGE THE PROJECT

- a. PHASE DEVELOPMENT PROJECTS TO THE MAXIMUM DEGREE PRACTICABLE AND TAKE INTO ACCOUNT SEASONAL WORK LIMITATIONS.
- b. INSPECTION AND MONITORING – INSPECT, MAINTAIN AND REPAIR ALL BMPS AS NEEDED TO ASSURE CONTINUED PERFORMANCE OF THEIR INTENDED FUNCTION. PROJECTS REGULATED UNDER THE CONSTRUCTION STORMWATER GENERAL PERMIT (CSWGP) MUST CONDUCT SITE INSPECTIONS AND MONITORING IN ACCORDANCE WITH SPECIAL CONDITION S4 OF THE CSWGP.
- c. MAINTAINING AN UPDATED CONSTRUCTION SWPPP.

ELEMENT 13 – PROTECT LOW IMPACT DEVELOPMENT (LID) BMPS

- a. THE PRIMARY PURPOSE OF LID BMPS/ON-SITE LID STORMWATER MANAGEMENT BMPS IS TO REDUCE THE DISRUPTION OF THE NATURAL SITE HYDROLOGY. LID BMPS ARE PERMANENT FACILITIES.
- b. PERMITTEES MUST PROTECT ALL BIORETENTION AND RAIN GARDEN FACILITIES FROM SEDIMENTATION THROUGH INSTALLATION AND MAINTENANCE OF EROSION AND SEDIMENT CONTROL BMPS ON PORTIONS OF THE SITE THAT DRAIN INTO THE BIORETENTION AND/OR RAIN GARDEN FACILITIES. RESTORE THE FACILITIES TO THEIR FULLY FUNCTIONING CONDITION IF THEY ACCUMULATE SEDIMENT DURING CONSTRUCTION. RESTORING THE FACILITY MUST INCLUDE REMOVAL OF SEDIMENT AND ANY SEDIMENT-LADEN BIORETENTION/RAIN GARDEN SOILS, AND REPLACING THE REMOVED SOILS WITH SOILS MEETING THE DESIGN SPECIFICATION.
- c. PERMITTEES MUST MAINTAIN THE INFILTRATION CAPABILITIES OF BIORETENTION AND RAIN GARDEN FACILITIES BY PROTECTING AGAINST COMPACTION BY CONSTRUCTION EQUIPMENT AND FOOT TRAFFIC. PROTECT COMPLETE LAWN AND LANDSCAPED AREAS FROM COMPACTION DUE TO CONSTRUCTION EQUIPMENT.
- d. PERMITTEES MUST CONTROL EROSION AND AVOID INTRODUCING SEDIMENT FROM SURROUNDING LAND USES ONTO PERMEABLE PAVEMENTS. DO NOT ALLOW MUDDY CONSTRUCTION EQUIPMENT ON THE BASE MATERIAL OR PAVEMENT. DO NOT ALLOW SEDIMENT-LADEN RUNOFF ONTO PERMEABLE PAVEMENTS.
- e. PERMITTEES MUST CLEAN PERMEABLE PAVEMENTS FOULED WITH SEDIMENTS OR NO LONGER PASSING AN INITIAL INFILTRATION TEST USING LOCAL STORMWATER MANUAL METHODOLOGY OR THE MANUFACTURER'S PROCEDURES.
- f. PERMITTEES MUST KEEP ALL HEAVY EQUIPMENT OFF EXISTING SOILS UNDER LID FACILITIES THAT HAVE BEEN EXCAVATED TO FINAL GRADE TO RETAIN THE INFILTRATION RATE OF THE SOILS.




DAVID EVANS
AND ASSOCIATES INC.


PROJECT NO.: E0214-S		FED. AID NO.: 4850DRWA #674680		DRAWN BY: R.S.B.		DESIGNED BY: R.S.B.		CHECKED BY: R.W.		APPROVED BY: R.W.		PROJECT LOCATED NEAR: CONCRETE, WA		S 14 T 34 N R 9 E					
CONCRETE SAUK VALLEY ROAD		CULVERT REPAIR PROJECT -		SOUTH OSTERMAN CREEK		TESC NOTES & SWPPP ELEMENTS		1 INCH SCALE BAR ADJUST SCALE ACCORDINGLY		SHEET 3 OF 30		NO.		REVISIONS		DATE			
DESIGN ENGINEER		ENGINEER OF RECORD		PROJECT NO.: E0214-S		FED. AID NO.: 4850DRWA #674680		DRAWN BY: R.S.B.		DESIGNED BY: R.S.B.		CHECKED BY: R.W.		APPROVED BY: R.W.		PROJECT LOCATED NEAR: CONCRETE, WA		S 14 T 34 N R 9 E	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.		REVISIONS		DATE		NO.	
NO.		REVISIONS																	

TEMPORARY TRAFFIC CONTROL NOTES:

1. THE DETOUR PROPOSED AS PART OF THIS TEMPORARY TRAFFIC CONTROL PLAN IS EXPECTED TO LAST 60 WORKING DAYS, OR THREE MONTHS. SUBSTANTIAL COMPLETION OF THE WORK SHOULD BE DONE BY THE CLOSING OF THE FISH WINDOW IN LATE SEPTEMBER 2026.
2. ALL TEMPORARY TRAFFIC CONTROL SHALL BE IN ACCORDANCE WITH THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD) SECTION 6 AND THE WSDOT STANDARD SPECIFICATIONS FOR ROAD, BRIDGE, AND MUNICIPAL CONSTRUCTION.
3. ALL SIGNS SHALL BE PER WSDOT SIGN FABRICATION MANUAL, UNLESS OTHERWISE SPECIFIED. DIAMOND SHAPED SIGNS WITHIN WSDOT ROW SHALL BE 48IN X 48IN. SIGNS OUTSIDE OF WSDOT ROW MAY BE 36IN X 36IN.
4. REMOVE CONFLICTING EXISTING PAVEMENT MARKINGS AND SECURELY COVER CONFLICTING EXISTING SIGNS.
5. A MINIMUM OF 5 CHANNELIZATION DEVICES SHALL BE USED ON TAPERS. TYPE C STEADY BURNING LIGHTS ARE REQUIRED ON ALL CHANNELIZING DEVICES USED DURING HOURS OF DARKNESS.
6. THE CONTRACTOR SHALL INSTALL AND REMOVE UPON COMPLETION OF WORK ALL NECESSARY TEMPORARY TRAFFIC CONTROL SIGNAGE, AS NOTED ON THESE PLANS.
7. NOTIFY THE FOLLOWING ENTITIES 14 DAYS PRIOR TO ANY LANE CLOSURE OR ACCESS CHANGES:
 - SKAGIT COUNTY PUBLIC WORKS DEPARTMENT
 - SKAGIT COUNTY FIRE DISTRICT 10
 - SKAGIT COUNTY SHERIFF DEPARTMENT
 - WASHINGTON STATE DEPARTMENT OF TRANSPORTATION
 - CONCRETE SCHOOL DISTRICT
 - WASTE MANAGEMENT OF WASHINGTON INC.
 - UNITED STATES POSTAL SERVICE
 - SNOHOMISH COUNTY PUBLIC WORKS DEPARTMENT
8. DEVICES SHALL NOT ENCRoACH INTO ADJACENT VEHICLE LANES OR DRIVEWAYS.
9. THE CONTRACTOR SHALL BE RESPONSIBLE IN PROVIDING SIGNS AT ALL TIMES DURING CONSTRUCTION. ANY DAMAGE TO ROADS OR PROPERTY ALONG CONCRETE-SAUK VALLEY RD, CAUSED BY CONTRACTOR ACTIVITIES SHALL BE ALL FIXED AT CONTRACTOR'S COST.
10. CONCRETE-SAUK VALLEY RD SOUTH OF SAUK RIVER PARK RD AND NORTH OF FINNEY CREEK RD AND SHALL REMAIN OPEN TO PUBLIC ACCESS DURING CONSTRUCTION.



TYPE 3 BARRICADE DETAIL
N.T.S.



CHANNELIZING DEVICE SPACING

POSTED SPEED (MPH)	IN TAPER (FEET)	IN TANGENT (FEET)
50 / 60	50	100
35 / 45	40	80
25 / 30	20	40

MINIMUM TAPER LENGTH = L (FEET)

LANE WIDTH (FEET)	25	30	35	40	45	50	55	60
10	105	150	205	270	450	500	550	-
11	115	165	225	294	495	550	605	660
12	125	180	245	320	540	600	650	720

PCMS

PANEL 1					PANEL 2				
C	S	V	R	D	S	T	A	R	T
C	L	O	S	E	D	M	M	I	D
A	T	M	P	1	3				
2 SEC					2 SEC				

SCENARIO "A"

MEANING OF LETTER CODES ON APPLICATION DIAGRAM

ROAD TYPE	DISTANCE BETWEEN SIGNS		
	A	B	C
URBAN (LOW SPEED)	100	100	100
URBAN (HIGH SPEED)	350	350	350
RURAL	500	500	500

PCMS

PANEL 1					PANEL 2				
C	S	V	R	D	F	O	L	L	O
C	L	O	S	E	D	D	E	T	O
A	T	M	P	1	3	R	O	U	T
2 SEC					2 SEC				

SCENARIO "B"

PORTABLE CHANGEABLE MESSAGE SIGN DETAIL

N.T.S.

APPROVAL EXPIRES 6 MONTHS
AFTER DATE SIGNED

ACCEPTED AS NOTED
Chatter Steen
11/07/2025
WSDOT TRAFFIC OPERATIONS

Within WSDOT Right-of-Way/Limited Access Only
LOCAL AGENCY Shall Also Accept

EXHIBIT "B"

Sheet 1 of 4

SKAGIT COUNTY
PUBLIC WORKS
1800 CONTINENTAL PLACE
MOUNT VERNON, WA 98273-5625
(360) 416-1400





PROJECT NO. E0214-5
FED AID NO. 4650DR-WA #674680
DESIGNED BY: --- DRAWN BY: ---
CHECKED BY: R.W. APPROVED BY: R.W.
PROJECT LOCATED NEAR:
CONCRETE, WA
S14T34NR9E

CONCRETE SAUK VALLEY ROAD
FISH PASSAGE PROJECT -
SOUTH OSTERMAN CREEK
TEMPORARY TRAFFIC CONTROL PLAN (1 OF 4)

1 INCH SCALE BAR
ADJUST SCALE ACCORDINGLY
SHEET
4 OF 30





WSDOT Notes:

1. Notify WSDOT CTCO 5 days before starting Work by contacting austin.bighorse@wsdot.wa.gov or (206) 440-4430.
2. At time of Work, call WSDOT Radio at (206) 440-4490 when lane/shoulder is closed, and again when lane/shoulder is opened. Leave contact name and mobile phone number with WSDOT Radio.
3. Notify Transit Agency(ies) & affected businesses 5 days prior to beginning Work.
4. Pedestrians and bicyclists shall be accommodated through the work zone. Assistance or signed detour shall be provided.
5. Only essential equipment and materials shall be on WSDOT R/W during working hours. No equipment or materials shall be on WSDOT R/W during non-working hours.
6. Channelization devices shall be Traffic Safety Drums with Type C Lights OR 6" Retro reflective bands meeting WSDOT Standard Specs.
7. During non-Working hours, area shall meet criteria in WSDOT Std Specs. 1-07 23, including, but not limited to, "drop off" protection.
8. All W-Series signs shall be 48"x48" Black on Orange.
9. All R-Series signs shall be Black on White.
10. Flagging Station shall be visible from W20-7A. Add additional W20-7A if needed due to limited sight distance.
11. When side street or cross street falls within the sign sequence, signs shall also be placed on the side streets.
12. Lane/Shoulder closure hours for installing signs class A shall be Sunday through Thursday 9:00 PM to 5:00 AM nightly. Road closure days and hours shall be deferred to local agency.

Holiday Impacts:
No closures will be allowed from noon the day prior to a holiday or holiday weekend through noon the day following a holiday or holiday weekend. It is a holiday weekend when the holiday falls on a Friday, Saturday, Sunday, or Monday.

GENERAL NOTES

1. SIGN SPACING SHALL BE ADJUSTED TO FIT INTERSECTIONS AND DRIVEWAYS.
2. CONTRACTOR SHALL STAGE WORK TO MINIMIZE DISRUPTION TO LOCAL RESIDENTS & EMERGENCY SERVICES.
3. FOR INSTALLING AND REMOVING SIGNS ALONG SR20 AND ANY OTHER ROUTES WITH NARROW SHOULDERS, USE THE SINGLE LANE CLOSURE DETAIL TOP 1 ON PAGE 7. FOR ALL OTHER ROUTES USE THE SHOULDER CLOSURE DETAIL TOP 10.

CONSTRUCTION NOTES

1. INSTALL SIGN(S) ON 4IN X 4IN WOOD POST WHERE APPROPRIATE, PER WSDOT STD PLAN G-22.10.
2. INSTALL TYPE 3 BARRICADES AND SIGN(S) PER WSDOT STANDARDS.
3. INSTALL SIGN ON STEEL TRIPOD SECURED WITH SANDBAGS WHERE APPROPRIATE.

LEGEND

#

CONSTRUCTION NOTE

#

SIGN NUMBER

WORK ZONE

APPROVAL EXPIRES 6 MONTHS AFTER DATE SIGNED

ACCEPTED AS NOTED

11/07/2025
WSDOT TRAFFIC OPERATIONS

Within WSDOT Right-of-Way/Limited Access Only
LOCAL AGENCY Shall Also Accept

NAVD 88

SCALE:
1" = N/A
1" = N/A

DAVID EVANS AND ASSOCIATES INC.

SKAGIT COUNTY PUBLIC WORKS
1800 CONTINENTAL PLACE
MOUNT VERNON, WA 98273-5625
(360) 416-1400

NO.	REVISIONS	DATE

11-5-2025

PROJECT NO: E0214-5
FED AID NO: 4650DR-WA #674680
DESIGNED BY: -
CHECKED BY: R.W.
DRAWN BY: -
APPROVED BY: R.W.





PROJECT LOCATED NEAR:
CONCRETE, WA
S 14 T 34 N R 9 E

CONCRETE SAUK VALLEY ROAD
FISH PASSAGE PROJECT -
SOUTH OSTERMAN CREEK

TEMPORARY TRAFFIC CONTROL PLAN (2 OF 4)

1 INCH SCALE BAR
ADJUST SCALE ACCORDINGLY

SHEET
5 OF 30



WSDOT Notes on Sheet 5 of 30.

GENERAL NOTES

1. SIGN SPACING SHALL BE ADJUSTED TO FIT INTERSECTIONS AND DRIVEWAYS.
2. CONTRACTOR SHALL STAGE WORK TO MINIMIZE DISRUPTION TO LOCAL RESIDENTS & EMERGENCY SERVICES.
3. FOR INSTALLING AND REMOVING SIGNS ALONG SR20 AND ANY OTHER ROUTES WITH NARROW SHOULDERS, USE THE SINGLE LANE CLOSURE DETAIL TCP 1 ON PAGE 7. FOR ALL OTHER ROUTES USE THE SHOULDER CLOSURE DETAIL TCP 10.

CONSTRUCTION NOTES

1. INSTALL SIGN(S) ON 4IN X 4IN WOOD POST WHERE APPROPRIATE, PER WSDOT STD PLAN G-22.10.
2. INSTALL TYPE 3 BARRICADES AND SIGN(S) PER WSDOT STANDARDS.
3. INSTALL SIGN ON STEEL TRIPOD SECURED WITH SANDBAGS WHERE APPROPRIATE.

LEGEND

- # CONSTRUCTION NOTE
- # SIGN NUMBER
- WORK ZONE
- TYPE 3 BARRICADES AS NECESSARY TO BLOCK ROAD
- CLASS "A" CONSTRUCTION SIGN
- CLASS "B" CONSTRUCTION SIGN
- DIRECTION OF TRAFFIC FLOW
- CHANNELIZATION DEVICE
- PCMS PORTABLE CHANGEABLE MESSAGE SIGN
- FLAGGER STATION

APPROVAL EXPIRES 6 MONTHS AFTER DATE SIGNED

ACCEPTED AS NOTED
Chatter Stea
 11/07/2025
 WSDOT TRAFFIC OPERATIONS

Within WSDOT Right-of-Way/Limited Access Only
 LOCAL AGENCY Shall Also Accept



SCALE:
 1" = N/A
 1" = N/A



EXHIBIT " B "
 Sheet 3 of 4

**SKAGIT COUNTY
PUBLIC WORKS**
 1800 CONTINENTAL PLACE
 MOUNT VERNON, WA 98273-5625
 (360) 416-1400

NO.	REVISIONS	DATE



DESIGN ENGINEER
 ENGINEER OF RECORD

PROJECT NO.: E0214-5	DRAWN BY: -
FED AID NO.: 4650DR-WA 1674680	CHECKED BY: R.W.
DESIGNED BY: -	APPROVED BY: R.W.
PROJECT LOCATED NEAR: CONCRETE, WA	S 14 T 34 N R 9 E

CONCRETE SAUK VALLEY ROAD
 FISH PASSAGE PROJECT -
 SOUTH OSTERMAN CREEK
 TEMPORARY TRAFFIC CONTROL PLAN (3 OF 4)

1 INCH SCALE BAR
 ADJUST SCALE ACCORDINGLY
 SHEET
 6 OF 30

Accommodate same warning sign sequence and spacing X before flagging station

WSDOT Notes on Sheet 5 of 30.

PCMS

50' to 100'
6 DEVICE MIN

50' TO 100'

50 MPH

BE PREPARED TO STOP

W20-7A

W20-7B (OPTIONAL IF 40 MPH OR LESS)

ROAD WORK AHEAD

ONE LANE ROAD AHEAD

W20-1

W20-4

PCMS

SIGN SPACING = X (1)

RURAL HIGHWAYS	60-65 MPH	800' +/-
RURAL ROADS	45-55 MPH	500' +/-
RURAL ROADS & URBAN ARTERIALS	35-40 MPH	350' +/-
RURAL ROADS & URBAN ARTERIALS RESIDENTIAL & BUSINESS DISTRICTS	25-30 MPH	200' +/- (2)
URBAN STREETS	25 MPH OR LESS	100' +/- (2)

(1) ALL SPACING MAY BE ADJUSTED TO ACCOMMODATE INTERSECTIONS AND DRIVEWAYS.
(2) THIS SPACING MAY BE REDUCED IN URBAN AREAS TO FIT ROADWAY CONDITIONS.
ALL SIGNS ARE 48" X 48" BLACK ON ORANGE UNLESS OTHERWISE DESIGNATED

LONGITUDINAL BUFFER SPACE = B

SPEED (MPH)	20	25	30	35	40	45	50	55	60	65
LENGTH (feet)	115	155	200	250	305	360	425	495	570	645

PROTECTIVE VEHICLE ROLL AHEAD DISTANCE = R
NO SPECIFIED DISTANCE REQUIRED
STRATEGICALLY POSITION WORK VEHICLE TO PROTECT WORK CREW

STATIONARY TRANSPORTABLE ATTENUATOR ROLL AHEAD DISTANCE = R
HOST VEHICLE WEIGHT
9,900 TO 22,000 lbs
UP TO 40 MPH 45-55 MPH 60+ MPH
100' 123' 172' 74' 100' 150'

MAXIMUM CHANNELIZATION DEVICE SPACING (feet)

MPH	TAPER	TANGENT
50-65	20	80
35-45	20	60
20-30	20	40

NOTES

- Night work requires additional roadway lighting at flagging stations.
- Recommend extending channelizing device taper across shoulder. Channelizing devices at flagger stations recommended.
- Protective Vehicle recommended and may be a work vehicle strategically located to shield the work area.
- For low-volume roadways with short-duration work zones on straight roadways where the flagger is visible to road users approaching from both directions a single flagger, positioned to be visible from both directions may be used.
- Extend the buffer space to locate the flagger station in advance of a curve, if necessary.
- Flaggers shall provide control and direction for pedestrians.
- Sign sequence is the same for both directions of travel on the roadway.

TYPICAL ONE-LANE, TWO-WAY TRAFFIC CONTROL WITH FLAGGERS
APPLICABLE FOR CLASS "A" SIGN INSTALL AT THE INTERSECTION OF:
SR20 & SR530
SR20 & CONCRETE SAUK VALLEY ROAD
SR530 & CONCRETE SAUK VALLEY ROAD
SOUTH SKAGIT HIGHWAY & CONCRETE SAUK VALLEY ROAD

LEGEND

FLAGGING STATION

SIGN LOCATION

CHANNELIZING DEVICES

PROTECTIVE VEHICLE

PCMS

Phase 1 - Shoulder work
Phase 2 - 1 mile ahead

50 MPH

2 MIN

WORK AREA

100'

200' UPSTREAM

PCMS

ROAD WORK AHEAD

SHOULDER WORK

SHOULDER CLOSED

W20-1

W21-5

W20-301

NOTES

- No encroachment on traveled lane if encroachment is necessary, lane shall be closed. The 2' lateral buffer is recommended.
- When used, device spacing for the downstream taper should be 20' O.C.
- If shoulder is used for traveled lanes at certain times, use full L taper and TMA.
- TMA required for freeways.

LEGEND

SIGN LOCATION

CHANNELIZING DEVICES

TMA

TYPICAL SHOULDER CLOSURE - HIGH SPEED (45 MPH OR HIGHER)

APPLICABLE FOR CLASS "A" SIGN INSTALL ON:
SR20 MP88 - MP98
SR530 MP61 - MP68
CONCRETE SAUK VALLEY ROAD MP0 - MP16
SOUTH SKAGIT HIGHWAY MP23 - MP24

An 8-foot paved shoulder is required to implement a shoulder closure only. The truck-mounted attenuator (TA) must be parked on full-width pavement to ensure crash-worthiness. If the location lacks an 8-foot shoulder, a flagging operation must be used instead.


APPROVAL EXPIRES 6 MONTHS
AFTER DATE SIGNED

ACCEPTED AS NOTED
Christopher Steen
11/07/2025
WSDOT TRAFFIC OPERATIONS

Within WSDOT Right-of-Way/Limited Access Only
LOCAL AGENCY Shall Also Accept

EXHIBIT " B "
Sheet 4 of 4

MAMI - November 4, 2025 - 9:43 PM - P:\S\SKAGIT\0000031\0400CAD\SHEETS\000 CAD-2020\010 DRAWING\B-CIVIL SHEET\2017028_TC_SO.DWG



PROJECT LIMIT
STA. 219+18.75
N.526324.546
E.1454009.140

REFER TO SHEETS 17 AND 27
FOR ALIGNMENT INFORMATION

PROJECT LIMIT
STA. 100+00
N.526242.861
E.1454214.466

PROJECT LIMIT
STA. 215+71.93
N.526401.299
E.1454329.180

PROPOSED TEMPORARY CONSTRUCTION EASEMENT ACQUISITION

PARCEL ID	PARCEL #	PROPERTY OWNER(S)	OWNER MAILING ADDRESS	LOT AREA (SQ FT)	TEMPORARY CONSTRUCTION EASEMENT (SQ FT)	REMAINING AREA (SQ FT)
1	P30970	LORI D. MANNING	17705 67TH AVE E, PUYALLUP, WA 98375	±99,317	±33,394	±65,923
2	P30972	SIERRA PACIFIC LAND & TIMBER CO.	PO BOX 496028, REDDING, CA 96049	±2,592,383	±19,755	±2,572,628


PROJECT LIMIT
STA. 104+00.00
N. 526608.175
E. 1454079.430

EROSION CONTROL KEYNOTES

1. PRESERVING NATURAL VEGETATION (BMP C101).
2. SITE REVEGETATION SHALL CONFORM TO THE SPECIAL PROVISIONS AND SHEETS 25 & 26
3. MATERIALS DELIVERY, STORAGE & CONTAINMENT (BMP C153)
4. STREET CLEANING (BMP C107)
5. DUST CONTROL (BMP C140)
6. SURFACE ROUGHENING (BMP C130)
7. MAINTAIN ACCESS DURING CONSTRUCTION.
8. SEEDING & MULCHING (BMP C120 & C121). MULCHING SHALL BE "LONG-TERM MULCH" MEETING THE SPECIFICATIONS OF 9-14.5(2)A OF THE STANDARD SPECIFICATIONS.
9. DRIVEWAY LOCATION NOT SURVEYED BY LICENSED SURVEYOR. CONTRACTOR TO FIELD VERIFY LOCATION.

LEGEND

- HIGH VISIBILITY FENCE (BMP C103)
- SAW-CUTTING LIMITS (BMP C152)
- STABILIZED CONSTRUCTION ENTRANCE (C105)
- WATTLES (BMP C235)
- LIMITS OF VEGETATION REMOVAL
- DITCH
- TRIANGULAR SILT DIKE (BMP C208)
- DRAINAGE FLOW DIRECTION ARROWS (SHEET FLOW, OR SHALLOW CHANNEL FLOW) ON ROADWAY.
- DRAINAGE FLOW DIRECTION ARROWS (SHEET FLOW, OR SHALLOW CHANNEL FLOW) OFF ROADWAY.



* NOTE: FOR FILL CONDITIONS 4'
FOR CUT CONDITIONS 4' TO 9'

DETAIL "A" HVF
INSTALLATION (TYP)
N.T.S




SCALE:
1" = 20' HOR
1" = N/A



SKAGIT COUNTY
PUBLIC WORKS

1800 CONTINENTAL PLACE
MOUNT VERNON, WA 98273-5625
(360) 416-1400



DESIGN ENGINEER


ENGINEER OF RECORD

PROJECT NO.: EO214-5
FED. AID NO.: 4850DRWA #674680
DESIGNED BY: R.S.B.
CHECKED BY: T.M.W.
DRAWN BY: R.S.B.
APPROVED BY: T.M.W.
PROJECT LOCATED NEAR:
CONCRETE, WA
S 14 T 34 N R 9 E

CONCRETE SAUK VALLEY ROAD
CULVERT REPAIR PROJECT -
SOUTH OSTERMAN CREEK

TESC PLAN

1 INCH SCALE BAR
ADJUST SCALE ACCORDINGLY
SHEET
8 OF 30



PROJECT LIMIT
STA. 219+18.75
N.526324.546
E.1454009.140

C & G STAKING POINTS.		C & G STAKING POINTS.		C & G STAKING POINTS.	
NORTHING	EASTING	NORTHING	EASTING	NORTHING	EASTING
526272.060	1454124.852	526338.094	1454196.585	526393.595	1454049.942
526282.256	1454240.310	526351.158	1454099.215	526402.856	1454351.948
526298.074	1454226.442	526351.316	1454001.240	526404.894	1454286.963
526298.166	1454114.129	526354.703	1454179.606	526406.470	1454235.351
526309.929	1454016.185	526368.883	1454010.862	526422.540	1454057.830
526317.747	1454211.112	526373.939	1454336.818	526424.765	1454274.595
526318.850	1454030.684	526381.807	1454024.100	526439.352	1454242.175
526321.211	1454104.437	526386.627	1454192.776	526447.467	1454074.794
526332.457	1453999.070	526389.423	1454304.959	526455.784	1454171.324
526333.675	1454050.241	526391.155	1454217.278	526455.963	1454355.241

- GENERAL NOTES
1. REMOVAL OF ALL EXIST. DRAINAGE FEATURES SHALL BE COORDIATED WITH THE TEMPORARY EROSION CONTROL PLANS AND SITE ISOLATION & DEWATERING PLANS.
- xx SITE PREPARATION NOTES
1. PRESERVE & PROTECT EXIST BURIED POWER & TELECOM UTILITY.
2. PRESERVE & PROTECT EXIST SIGN & POST.
3. PRESERVE EXIST TREE.
4. PRESERVE EXIST CHANNELIZATION MARKINGS.
5. MAINTAIN HOMEOWNER ACCESS THROUGHOUT CONSTRUCTION. SEE TRAFFIC CONTROL PLANS.
6. REMOVE & DISPOSE OF EXIST CULVERT AS PART OF STRUCTURE EXCAVATION CLASS A.
7. REMOVE & SALVAGE EXIST SIGN & POST.
8. REMOVE & SALVAGE EXIST TREE FOR FUTURE USE.
9. CLEAR & GRUB TO LIMITS OF THE TABLES SHOWN. NO SIGNIFICANT TREES (6 INCHES DBH) SHALL BE REMOVED BEYOND CLEARING LIMITS. REUSE WOODY MATERIAL GENERATED THROUGH CLEARING NON-INVASIVE SPECIES AS REQUIRED IN THE SPECIAL PROVISIONS.
10. SAWCUT EX. PVMT PER SEC. 2-03. EXIST PVMT THICKNESS UNKNOWN. ESTIMATED TO BE 3 INCHES ±.

LEGEND

- LIMITS OF ASPHALT REMOVAL
- LIMITS OF CLEARING & GRUBBING (C&G)
- LIMITS OF TEMPORARY CONSTRUCTION EASEMENT

PROJECT LIMIT
STA. 104+00.00
N. 526608.175
E. 1454079.430

REMOVE EXISTING
EMBANKMENT
STABILIZATION
MEASURES

C & G STAKING POINTS.		C & G STAKING POINTS.	
NORTHING	EASTING	NORTHING	EASTING
526463.909	1454150.667	526513.575	1454204.572
526475.406	1454066.943	526519.313	1454224.306
526478.338	1454344.089	526520.795	1454269.789
526487.517	1454146.752	526521.986	1454256.553
526488.278	1454186.700	526522.088	1454245.800
526492.513	1454331.209	526533.793	1454053.188
526495.887	1454298.168	526562.637	1454044.742
526504.552	1454140.509	526598.392	1454041.235
526504.629	1454059.973		
526508.266	1454292.254		

SCALE:
1" = 20' HOR
1" = N/A



NAVD 88



SKAGIT COUNTY
PUBLIC WORKS

1800 CONTINENTAL PLACE
MOUNT VERNON, WA 98273-5625
(360) 416-1400

DESIGN ENGINEER

ENGINEER OF RECORD

PROJECT NO.: EO214-S
FED. AID NO.: 4650DRWA #674680
DESIGNED BY: R.S.B.
CHECKED BY: T.M.W.

DATE
9-29-25

NO.

REVISIONS

CONCRETE SAUK VALLEY ROAD
CULVERT REPAIR PROJECT -
SOUTH OSTERMAN CREEK


SITE PREPARATION PLAN

1 INCH SCALE BAR
ADJUST SCALE ACCORDINGLY

SHEET
9 OF 30

PROJECT LOCATED NEAR:
CONCRETE, WA
S 14 T 34 N R 9 E

DAVID EVANS
AND ASSOCIATES INC.



NOTES:

1. ALL GRADING AND CHANNEL WORK BELOW THE ORDINARY HIGH WATER MARK SHALL BE ISOLATED FROM ACTIVELY FLOWING SURFACE WATERS.
2. THE TEMPORARY STREAM DIVERSION APPROACH SHOWN ON THIS SHEET IS ONE EXAMPLE OF AN ACCEPTABLE APPROACH FOR DIVERTING WATER AROUND THE WORK AREA. THE CONTRACTOR SHALL SUBMIT A TEMPORARY STREAM DIVERSION PLAN FOR REVIEW AS REQUIRED IN SECTION 8-31 OF THE STANDARD SPECIFICATIONS.
3. THE CONTRACTOR SHALL CLOSELY COORDINATE WITH THE ENGINEER REGARDING SCHEDULE AND IMPLEMENTATION OF TEMPORARY STREAM DIVERSION ELEMENTS AS REQUIRED IN SECTION 8-31 OF THE STANDARD SPECIFICATIONS AND ALLOW FOR SCHEDULING OF FISH REMOVAL. NO WORK SHALL BE PERFORMED WITHIN THE ISOLATED WORK AREA, INCLUSIVE OF DEWATERING, UNTIL FISH REMOVAL HAS BEEN COMPLETED.
4. THE CONTRACTOR IS REQUIRED TO DESIGN A CONTINGENCY TEMPORARY STREAM DIVERSION AS REQUIRED IN SECTION 8-31 OF THE SPECIAL PROVISIONS (NOT ILLUSTRATED ON THIS SHEET).
5. IN ADDITION TO TEMPORARY STREAM DIVERSION, THE CONTRACTOR IS ALSO RESPONSIBLE FOR DESIGNING AND IMPLEMENTING A TEMPORARY DEWATERING SYSTEM AS REQUIRED IN SECTION 6-20 OF THE SPECIAL PROVISIONS. THE DEWATERING PUMP SHOWN ON THIS SHEET IS INCLUDED FOR ILLUSTRATION PURPOSES ONLY; THE CONTRACTOR SHALL IMPLEMENT ELEMENTS OF THE DEWATERING SYSTEM AS DESIGNED BY THE CONTRACTOR ONCE THE DEWATERING SYSTEM WORKING DRAWINGS HAVE BEEN APPROVED BY THE ENGINEER.



Natural Systems Design
+ Coastal Geologic Services

CONCRETE SAUK VALLEY ROAD
CULVERT REPAIR PROJECT -
SOUTH OSTERMAN CREEK

SITE ISOLATION & DEWATERING

1 INCH SCALE BAR
ADJUST SCALE ACCORDINGLY

SHEET
10 OF 30

PROJECT NO.: EO214-5

FED. AID NO.: 4650DRWA #674680

DESIGNED BY: NT

CHECKED BY: DBS

APPROVED BY:


PROJECT LOCATED NEAR:

CONCRETE, WA

S 14 T 34 N R 9 E

COUNTY ENGINEER

ENGINEER OF RECORD




NO.

REVISIONS

DATE

SKAGIT COUNTY
PUBLIC WORKS

1800 CONTINENTAL PLACE
MOUNT VERNON, WA 98273-5625
(360) 416-1400




NOTES:

1. STREAM BYPASS INTAKE SHALL REST ON EXISTING STREAMBED.
2. PUMP INTAKE SHALL BE FITTED WITH FISH SCREEN MEETING APPLICABLE RCW SECTIONS (RCW 77.57.010 AND 77.57.070), AS WELL AS NMFS CRITERIA. SEE SECTION 7-06 FOR MORE INFORMATION.
3. PUMP CAPACITY SHALL BE SIZED TO CONVEY THE ENTIRETY OF STREAMFLOW WITHOUT DEWATERING THE CHANNEL OUTSIDE THE ISOLATED WORK AREA. VARIABLE PUMPING MAY BE REQUIRED. SEE PROJECT PERMITS AND SECTION 8-31 FOR MORE INFORMATION.

BYPASS PUMP INTAKE
NOT TO SCALE

1
11




NOTES:

1. CORRUGATED PLASTIC OR METAL PIPE 36" MIN DIAMETER PERFORATED PIPE, ONE PER EACH PUMP.
2. STREAMBED SEDIMENT.
3. LIMIT OF EXCAVATION. INSTALL PIPE AND BACKFILL WITH STREAMBED SEDIMENT.
4. PUMP INTAKE SHALL BE FITTED WITH FISH SCREEN MEETING RCW 77.57.010 AND RCW 77.57.070.
5. THE INTENT OF DEWATERING PUMPS IS TO REMOVE GROUNDWATER OR SURFACE WATER WHICH SEEPS INTO THE ISOLATED WORK AREA. DEWATERING PUMPS ARE OPTIONAL; IF USED, DEWATERING PUMPS SHALL BE OPERATED IN SUCH A WAY THAT NO PORTION OF THE STREAMBED OUTSIDE THE ISOLATED WORK AREA BECOMES DEWATERED.
6. THE DEWATERING PUMP INTAKE SHOWN ON THIS SHEET IS ONE EXAMPLE OF AN ELEMENT TO BE INCLUDED IN THE DEWATERING PLAN; ADDITIONAL ELEMENTS MAY BE REQUIRED TO DEWATER THE SITE AS REQUIRED IN THE SPECIAL PROVISIONS.
7. DIVERSION OF SURFACE FLOWS AND ALL DEWATERING SHALL BE CLOSELY COORDINATED AND TIMED WITH FISH EXCLUSION EFFORTS. DIVERSION OF SURFACE FLOWS AND/OR DEWATERING SHALL NOT OCCUR UNTIL FISH EXCLUSION EFFORTS HAVE BEEN COMPLETED.


DEWATERING PUMP INTAKE
NOT TO SCALE

2
11




ENERGY DISSIPATOR
NOT TO SCALE

3
11



COFFERDAM
NOT TO SCALE

4
11




SECTION A-A



Natural Systems Design
+ Coastal Geologic Services

SKAGIT COUNTY
PUBLIC WORKS
1800 CONTINENTAL PLACE
MOUNT VERNON, WA 98273-5625
(360) 416-1400

NO.	REVISIONS	DATE
1		




COUNTY ENGINEER

PROJECT NO.: E0214-S	DRAWN BY: DBS	APPROVED BY:
FED. AID NO.: 4650DRWA #674680	DESIGNED BY: NT	CHECKED BY:
PROJECT LOCATED NEAR: CONCRETE, WA S 14 T 34 N R 9 E		

CONCRETE SAUK VALLEY ROAD
CULVERT REPAIR PROJECT -
SOUTH OSTERMAN CREEK
SITE ISOLATION & DEWATERING DETAILS


1 INCH SCALE BAR
ADJUST SCALE ACCORDINGLY

SHEET
11 OF 30




SUPERELEVATION DIAGRAM - CONCRETE SAUK VALLEY ROAD


SCALE:
1" = 20' HOR
1" = 4' VER




A ROADWAY SECTION FOR STABILIZED CONSTRUCTION ENTRANCE
Scale: 1" = 4'




B ROAD TYPICAL SECTION FOR CONCRETE SAUK VALLEY RD (STA. 100+75.00 TO STA. 102+95.00)
Scale: 1" = 4'
** REFER TO SUPERELEVATION DIAGRAM ABOVE




C ROAD TYPICAL SECTION FOR CONCRETE SAUK VALLEY RD (STA. 100+00.00 TO STA. 100+75.00)
Scale: 1" = 4'
** REFER TO SUPERELEVATION DIAGRAM ABOVE



D ROAD TYPICAL SECTION FOR CONCRETE SAUK VALLEY RD (STA. 102+95.00 TO STA. 104+00.00)
Scale: 1" = 4'
** REFER TO SUPERELEVATION DIAGRAM ABOVE



E LONGITUDINAL BUTT-JOINT PLANING DETAIL
NTS



**SKAGIT COUNTY
PUBLIC WORKS**

1800 CONTINENTAL PLACE
MOUNT VERNON, WA 98273-5625
(360) 416-1400

DESIGN ENGINEER	ENGINEER OF RECORD	PROJECT NO.	FED. AID NO.	CHECKED BY	DESIGNED BY	DRAWN BY	APPROVED BY	PROJECT LOCATED NEAR	NO.	REVISIONS	DATE
		EO214-S	4650DRWA #674680	R.S.B.	R.S.B.	R.S.B.	R.S.B.	CONCRETE, WA	9-29-25		







PROJECT NO.: EO214-S	FED. AID NO.: 4650DRWA #674680	DESIGNED BY: R.S.B.	CHECKED BY: R.S.B.	DRAWN BY: R.S.B.	APPROVED BY: R.W.	PROJECT LOCATED NEAR: CONCRETE, WA
----------------------	--------------------------------	---------------------	--------------------	------------------	-------------------	------------------------------------

**CONCRETE SAUK VALLEY ROAD
CULVERT REPAIR PROJECT -
SOUTH OSTERMAN CREEK**


SUPERELEVATION DIAGRAM & TYPICAL
SECTIONS

1 INCH SCALE BAR
ADJUST SCALE ACCORDINGLY

SHEET
13 OF 30



SCALE:
1" = 10' HOR
1" = 10' VER



CONCRETE SAUK VALLEY ROAD
CULVERT REPAIR PROJECT -
SOUTH OSTERMAN CREEK

ROAD X-SECTIONS

PROJECT NO.: E0214-S
FED. AID NO.: 4650DRWA #674680
DESIGNED BY: R.S.B.
CHECKED BY: R.W.
DRAWN BY: R.S.B.
APPROVED BY: R.W.
PROJECT LOCATED NEAR:
CONCRETE, WA
S 14 T 34 N R 9 E

NO.	REVISIONS	DATE



SKAGIT COUNTY
PUBLIC WORKS
1800 CONTINENTAL PLACE
MOUNT VERNON, WA 98273-5625
(360) 416-1400

STRUCTURAL NOTES

1.

ALL MATERIAL AND WORKMANSHIP SHALL BE IN ACCORDANCE WITH THE REQUIREMENTS OF WSDOT'S MOST CURRENT EDITION OF "STANDARD SPECIFICATIONS FOR ROAD, BRIDGE, AND MUNICIPAL CONSTRUCTION."
2.

THE CULVERTS SHALL BE DESIGNED IN ACCORDANCE WITH THE REQUIREMENTS OF AASHTO'S LRFD BRIDGE DESIGN SPECIFICATIONS 10TH EDITION 2024.
3.

THE SEISMIC PEAK GROUND ACCELERATION OF 0.26 AND SITE CLASS E SHALL BE USED FOR THE SEISMIC DESIGN.
4.

LIVE LOAD (LL) AASHTO HL-93 + IM AS SHOWN.
5.

THE PRECAST CONCRETE SHALL BE CLASS 5000, 6000 OR 7000 SELF CONSOLIDATING CONCRETE (SCC). OTHER CONCRETE SHALL BE CLASS 4000.
6.

STEEL REINFORCING SHALL CONFORM TO ASTM A615 GRADE 60.
7.

SEGMENTAL PRECAST CONCRETE BOX CULVERT UNITS SHALL BE MANUFACTURED IN ACCORDANCE WITH THE ASTM C 786 AND WSDOT STANDARD SPECIFICATION SECTION 6-02.3(20). ALL JOINTS SHALL BE TONGUE AND GROOVE AND SEALED WITH JOINT SEALANT PER ASTM C990 AND WRAPPED WITH EXTERNAL SEALING BAND PER ASTM C877.
8.

ALL STEEL PLATES AND SHAPES SHALL BE ASTM A36 OR ASTM A 992. ALL BOLTS, NUTS AN WASHERS (UNLESS NOTED OTHERWISE) SHALL BE ASTM A 307 AND COMPLY WITH WSDOT STANDARD SPECIFICATION 9-16.3(4) AND RESIN BONDED ANCHORS SHALL BE ASTM A 193 GRADE 87, OR ASTM A449. ALL STEEL PLATES SHALL BE GALVANIZED IN ACCORDANCE WITH AASHTO M111 AFTER FABRICATION. BOLTS AND HARDWARE SHALL BE GALVANIZED IN ACCORDANCE WITH ASHTO M 232.
9.

UNLESS OTHERWISE SHOWN IN THE PLANS, CONCRETE COVER MEASURED FROM THE FACE OF CONCRETE TO THE FACE OF ANY REINFORCING STEEL SHALL BE 2" AT THE TOP OF THE ROOF DECK, 1½" AT THE BOTTOM OF THE ROOF DECK, 3" AT THE BOTTOM OF FOOTINGS, AND 2" AT ALL OTHER LOCATIONS.
10.


THE BACKFILL AT BOTH SIDES OF THE CULVERT TO BE PLACED IN IN ACCORDANCE TO WSDOT STANDARD SPECIFICATION 2-09.3(1)E. THE MAXIMUM FIELD HEIGHT DIFFERENCE MEASURED FROM SIDE TO SIDE SHALL BE NO MORE 2'-0". THE MAXIMUM FIELD HEIGHT DIFFERENCE MEASURED FROM SIDE TO SIDE SHALL NOT BE MORE THAN 2'-0".
11.

A FOUNDATION MATERIAL LAYER SHALL BE PLACED CONSISTING OF A MINIMUM OF 12 INCHES CRUSHED ROCK PRODUCT OR PERMEABLE BALLAST PER WSDOT STANDARD SPECIFICATION 9.03.9(2) AND CONFORMING TO THE REQUIREMENTS OF THE GEOTECHNICAL REPORT.
12.

ADDITIONAL OVER-EXCAVATION OF 1 TO 2 FEET MAY BE REQUIRED TO PROPERLY SUPPORT THE PLANNED STRUCTURES IF EXCESSIVELY SOFT, ORGANIC, OR OTHERWISE UNSUITABLE SOILS ARE ENCOUNTERED AT THE SUBGRADE ELEVATION.
13.

CONTRACTOR MAY ENCOUNTER GROUNDWATER DURING CULVERT EXCAVATION OF AND SHALL PROVIDE DEWATERING OF EXCAVATIONS AND PROPERLY DISPOSE OF THIS WATER PER THE SPECIAL PROVISIONS.
14.

ALL GEOTECHNICAL RECOMMENDATIONS ARE INCLUDED IN THE REPORT BY GEOENGINEERS DATED 10/11/2021 MADE PART OF THESE CONTRACT DOCUMENTS.



LOADING DIAGRAM



CONCRETE SAUK VALLEY ROAD
CULVERT REPAIR PROJECT -
SOUTH OSTERMAN CREEK

STRUCTURAL NOTES

1 INCH SCALE BAR
ADJUST SCALE ACCORDINGLY

SHEET
15 OF 30


PROJECT NO.: EO214-S
FED.AID NO.: 4850DR-WA #674680
DESIGNED BY: P.S.S.
CHECKED BY: T.M.W.
PROJECT LOCATED NEAR:
CONCRETE, WA
S 14 T 34 N R 9 E

DESIGN ENGINEER
P.L. CHILDS
WASHINGTON
REGISTERED PROFESSIONAL
25945
11/3/25


ENGINEER OF RECORD
P.L. CHILDS
WASHINGTON
REGISTERED PROFESSIONAL
25945
11/3/25

SKAGIT COUNTY
PUBLIC WORKS
1800 CONTINENTAL PLACE
MOUNT VERNON, WA 98273-5625
(360) 416-1400

REVISIONS
NO.
DATE



CULVERT PLAN




CULVERT ELEVATION
LOOKING AHEAD ON STATION

GENERAL SHEET NOTES


1. CABLE FENCE MOUNTED ON TOP OF ALL HEADWALLS AND WING WALLS TO BE CONSTRUCTED PER WSDOT STANDARD DETAILS 8.1-A6-2, 8.1-A6-3, 8.1-A6-4, & 8.1-A6-5.

LEGEND

- INDEX CONTOUR
- INTERMEDIATE CONTOUR
- PRECAST WINGWALL
- PERMEABLE BALLAST
- UNSUITABLE FOUNDATION EXCAVATION INCL. HAUL




DETAIL "A"
N.T.S.



TYPICAL SECTION



SKAGIT COUNTY
PUBLIC WORKS
1800 CONTINENTAL PLACE
MOUNT VERNON, WA 98273-5625
(360) 416-1400



DESIGN ENGINEER
ENGINEER OF RECORD
PROJECT NO.: E0214-S
FED. AID NO.: 4650DRWA #674680
DESIGNED BY: P.S.S.
CHECKED BY: T.M.W.
DRAWN BY: D.J.J.
APPROVED BY: T.M.W.



PROJECT LOCATED NEAR:
CONCRETE, WA
S 14 T 34 N R 9 E


CONCRETE SAUK VALLEY ROAD
CULVERT REPAIR PROJECT -
SOUTH OSTERMAN CREEK
CULVERT PLAN & ELEVATION

1 INCH SCALE BAR
ADJUST SCALE ACCORDINGLY
SHEET
16 OF 30


SCALE:
1" = 5' HOR
1" = N/A









PLAN - SOUTH OSTERMAN CREEK CULVERT (WEST)



PLAN - SOUTH OSTERMAN CREEK CULVERT (EAST)



VIEW A - SOUTH OSTERMAN CREEK CULVERT (WEST)




VIEW B - SOUTH OSTERMAN CREEK CULVERT (EAST)



**SKAGIT COUNTY
PUBLIC WORKS**
1800 CONTINENTAL PLACE
MOUNT VERNON, WA 98273-5625
(360) 416-1400


NO.	REVISIONS	DATE



DESIGN ENGINEER
ENGINEER OF RECORD
PROJECT NO.: E0214-S
FED. AID NO.: 4650DRWA #674680
DESIGNED BY: P.S.S.
CHECKED BY: T.M.W.
DRAWN BY: D.J.J.
APPROVED BY: T.M.W.
PROJECT LOCATED NEAR:
CONCRETE, WA
S 14 T 34 N R 9 E

CONCRETE SAUK VALLEY ROAD
CULVERT REPAIR PROJECT -
SOUTH OSTERMAN CREEK
CULVERT HEADWALL LAYOUTS


1 INCH SCALE BAR
ADJUST SCALE ACCORDINGLY
SHEET
18 OF 30



CHANNEL PLAN

NOTES:

1. CHANNEL PLAN PRESENTED ON THIS SHEET REPRESENTS NEATLINE ELEVATIONS FOR CONSTRUCTION. ACTUAL FINISH GRADE WILL INCLUDE SIGNIFICANT VARIABILITY DUE TO LOGS, RACKING, AND STREAMBED BOULDERS AND COBBLES.
2. SEE SHEET 21 FOR TYPICAL CHANNEL SECTIONS AND STREAMBED MIX.
3. SEE SHEETS 26 THROUGH 28 FOR CHANNEL STRUCTURE DETAILS.
4. LOCATION OF DRIVEWAY IS APPROXIMATE. STAKEOUT AND APPROVAL OF GRADING LIMITS AND TIMBER HANDRAIL LOCATION IS REQUIRED PRIOR TO STARTING WORK.



Natural Systems Design
+ Coastal Geologic Services

CONCRETE SAUK VALLEY ROAD
CULVERT REPAIR PROJECT -
SOUTH OSTERMAN CREEK

CHANNEL PLAN

PROJECT NO.: EO214-S

FED. AID NO.: 4650DRAWA #674680

DESIGNED BY: NT

CHECKED BY:

DRAWN BY: DBS

APPROVED BY:

PROJECT LOCATED NEAR:

CONCRETE, WA

S 14 T 34 N R 9 E

COUNTY ENGINEER

ENGINEER OF RECORD



PROFESSIONAL 1/24/15

DATE

REVISIONS

NO.

DATE

REVISIONS


NO.

DATE

SKAGIT COUNTY
PUBLIC WORKS

1800 CONTINENTAL PLACE
MOUNT VERNON, WA 98273-5625
(360) 416-1400

SHEET
19 OF 30



CHANNEL LINE PROFILE

SCALE: 1"=20' HORIZ., 1"=4' VERT.


NOTES:

- CHANNEL PROFILE PRESENTED ON THIS SHEET REPRESENT NEATLINE ELEVATIONS FOR CONSTRUCTION. ACTUAL FINISH GRADE WILL INCLUDE SIGNIFICANT VARIABILITY DUE TO LOGS, RACKING, AND STREAMBED BOULDERS AND COBBLES.
- SEE SHEET 21 FOR TYPICAL CHANNEL SECTIONS AND STREAMBED MIX.
- SEE SHEETS 26 THROUGH 28 FOR CHANNEL STRUCTURE DETAILS.




Natural Systems Design
+ Coastal Geologic Services

CHANNEL STAKEOUT																				
STATION	LEFT									ℰ		RIGHT								
	DAYLIGHT			MIX		TOB		TOE		THWG		TOE		TOB		MIX		DAYLIGHT		
	OFFSET	ELEV.	C/F	OFFSET	ELEV.	OFFSET	ELEV.	OFFSET	ELEV.	OFFSET	ELEV.	OFFSET	ELEV.	OFFSET	ELEV.	OFFSET	ELEV.	OFFSET	ELEV.	C/F
219+81.8	10.7 L	293.2	CUT	10.5 L	293.1	8.5 L	293.1	7.0 L	292.1	0.0	291.4	7.0 R	292.1	8.5 R	293.1	10.5 R	293.1	12.4 R	293.1	FILL
219+75	11.3 L	293.2	CUT	10.5 L	292.8	8.5 L	292.8	7.0 L	291.8	0.0	291.1	7.0 R	291.8	8.5 R	292.8	10.5 R	292.8	11.6 R	292.8	FILL
219+50	14.1 L	293.3	CUT	10.5 L	291.5	8.5 L	291.5	7.0 L	290.5	0.0	289.8	7.0 R	290.5	8.5 R	291.5	10.5 R	292.5	10.6 R	292.6	CUT
219+25	20.8 R	296.4	CUT	10.5 L	291.3	8.5 L	290.3	7.0 L	289.3	0.0	288.6	7.0 R	289.3	8.5 R	290.3	10.5 R	291.3	12.1 R	292.1	CUT
219+00	26.3 R	298.0	CUT	10.5 L	290.0	8.5 L	289.0	7.0 L	288.0	0.0	287.3	7.0 R	288.0	8.5 R	289.0	10.5 R	290.0	13.7 R	290.0	FILL
218+75	25.9 L	296.5	CUT	10.5 L	288.8	8.5 L	287.8	7.0 L	286.8	0.0	286.1	7.0 R	286.8	8.5 R	287.8	10.5 R	288.8	12.4 R	289.7	FILL
CULVERT 0+00				10.5 L	288.3	7.7 L	287.0	6.2 L	286.0	1.0	285.4	8.5 R	286.3	10.1 R	287.3	10.5 R	287.5			
218+50				10.5 L	286.7	8.5 L	286.5	7.0 L	285.5	0.0	284.8	7.0 R	285.5	8.5 R	286.5	10.5 R	286.7			
218+25				10.5 L	285.5	8.5 L	285.3	7.0 L	284.3	0.0	283.6	7.0 R	284.3	8.5 R	285.3	10.5 R	285.5			
218+17.2				10.5 L	285.1	8.5 L	284.9	7.0 L	283.9	0.0	283.2	7.0 R	283.9	8.5 R	284.9	10.5 R	285.1			
218+00	30.3 L	287.1	FILL	13.7 L	284.6	11.7 L	284.2	9.0 L	283.2	0.0	282.3	11.4 R	283.4	12.9 R	284.5	14.9 R	285.5	25.4 R	290.8	CUT
217+88	34.2 L	286.5	FILL	17.9 L	284.1	15.9 L	283.7	13.3 L	282.6	0.0	281.7	14.8 R	282.8	16.7 R	284.0	18.7 R	285.0	22.8 R	287.0	CUT
217+75	20.0 L	284.0	FILL	19.5 L	283.7	17.5 L	283.3	15.0 L	282.1	0.0	281.1	15.0 R	282.1	17.5 R	283.3	19.5 R	283.5	25.1 R	284.1	FILL
217+60	21.3 L	284.5	CUT	19.5 L	283.6	17.5 L	282.6	15.0 L	281.3	0.0	280.3	15.0 R	281.3	17.5 R	282.6	19.5 R	282.8	36.5 R	284.0	FILL
217+50	22.4 L	284.5	CUT	19.5 L	283.1	17.5 L	282.1	15.0 L	280.8	0.0	279.8	15.0 R	280.8	17.5 R	282.1	19.5 R	282.3	21.2 R	283.9	CUT
217+38.8	25.8 L	285.7	CUT	19.5 L	282.5	17.5 L	281.5	15.0 L	280.3	0.0	279.3	15.0 R	280.3	17.5 R	281.5	19.5 R	282.5	24.0 R	284.8	CUT
217+25	28.5 L	286.8	CUT	19.5 L	282.3	17.5 L	281.3	15.0 L	280.0	0.0	279.0	15.0 R	280.0	17.5 R	281.3	19.5 R	282.3	23.9 R	284.5	CUT
217+15	29.3 L	287.0	CUT	19.5 L	282.1	17.5 L	281.1	15.0 L	279.8	0.0	278.8	15.0 R	279.8	17.5 R	281.1	19.5 R	282.1	23.8 R	284.2	CUT
217+00	46.1 L	295.1	CUT	19.5 L	281.8	17.5 L	280.8	15.0 L	279.5	0.0	278.5	15.0 R	279.5	17.5 R	280.8	19.5 R	281.8	23.9 R	283.9	CUT
216+75	42.6 L	292.8	CUT	19.5 L	281.3	17.5 L	280.3	15.0 L	279.0	0.0	278.0	15.0 R	279.0	17.5 R	280.3	19.5 R	281.3	25.2 R	284.1	CUT
216+50	29.0 L	285.5	CUT	19.5 L	280.8	17.5 L	279.8	15.0 L	278.5	0.0	277.5	15.0 R	278.5	17.5 R	279.8	19.5 R	280.8	23.4 R	282.7	CUT
216+25	41.4 L	291.2	CUT	19.5 L	280.3	17.5 L	279.3	15.0 L	278.0	0.0	277.0	15.0 R	278.0	17.5 R	279.3	19.5 R	280.3	23.7 R	282.4	CUT
216+00	25.7 L	282.9	CUT	19.5 L	279.8	17.5 L	278.8	15.0 L	277.5	0.0	276.5	15.0 R	277.5	17.5 R	278.8	19.5 R	279.8	21.5 R	280.8	CUT
215+92.4	23.7 L	281.7	CUT	19.5 L	279.6	17.5 L	278.6	15.0 L	277.4	0.0	276.4	15.0 R	277.4	17.5 R	278.6	19.5 R	279.6	25.4 R	280.5	FILL




STREAMBED MIX	
PERCENT PASSING	PARTICLE SIZE (IN)
100	48
84	26-30
50	7-11
16	0.75-1.5
10	0.25-0.5
5 MIN.	NO. 200 SIEVE

STREAMBED MIX DEPTH	
STATION RANGE	DEPTH
219+82 TO 218+61	4'-0"
218+61 TO 218+17	4'-0" MIN.
218+17 TO 217+39	4'-0"
217+39 TO 215+92	6'-0"
215+92 TO 215+75	5% MIX TO 4'-0" DEPTH



NOTES:

- SLASH MATERIAL SHALL BE INCORPORATED INTO STREAMBED MIX DURING CHANNEL CONSTRUCTION. SLASH MATERIAL SHALL BE APPROXIMATELY 5-10% OF THE CONSTRUCTED STREAMBED MIX BY VOLUME.
- PLACE STREAMBED MIX IN LIFTS OF NO MORE THAN 2 FEET. SEAL EACH LIFT BY WASHING IN FINE MATERIALS AND STREAMBED SAND, REFER TO SECTION 8-30 OF THE SPECIAL PROVISIONS.
- INDIVIDUAL PARTICLES GREATER THAN APPROXIMATELY 24 INCHES SHALL BE USED PRIMARILY TO FORM CHANNEL BANKS; PLACE AS DIRECTED BY THE ENGINEER.
- SECTION VIEWS AND STAKEOUT ARE ORIENTED LOOKING DOWNSTREAM IN THE CHANNEL AND DOWN-STATION RELATIVE TO THE ALIGNMENT.
- WOOD NOT SHOWN FOR CLARITY.



CHANNEL STAKEOUT POINTS	
THWG	LOWEST POINT OF CHANNEL SECTION, ON CENTERLINE
TOE	TOE OF CHANNEL BANK
TOB	TOP OF CHANNEL BANK
MIX	LIMIT OF STREAMBED MIX PLACEMENT
DAYLIGHT (CUT/FILL)	LIMIT OF EXCAVATION OR FILL PLACEMENT



Natural Systems Design
+ Coastal Geologic Services




ENGINEER OF RECORD
COUNTY ENGINEER
SKAGIT COUNTY PUBLIC WORKS
1800 CONTINENTAL PLACE
MOUNT VERNON, WA 98273-5625
(360) 416-1400

DATE
REVISIONS
NO.



PROJECT NO.: EO214-5
FED. AID NO.: 4850DRWA #674680
DESIGNED BY: NT
CHECKED BY:
DRAWN BY: DBS
APPROVED BY:
PROJECT LOCATED NEAR:
CONCRETE, WA
S 14 T 34 N R 9 E

CONCRETE SAUK VALLEY ROAD
CULVERT REPAIR PROJECT -
SOUTH OSTERMAN CREEK
TYPICAL CHANNEL SECTIONS



1 INCH SCALE BAR
ADJUST SCALE ACCORDINGLY
SHEET
21 OF 30





- NOTES
- ALL SECTION VIEWS ARE ORIENTED LOOKING DOWNSTREAM IN THE CHANNEL AND DOWN-STATION RELATIVE TO THE ALIGNMENT.
 - WOOD NOT SHOWN FOR CLARITY.



TIMBER HANDRAIL
4
28



- NOTES
1. ALL SECTION VIEWS ARE ORIENTED LOOKING DOWNSTREAM IN THE CHANNEL AND DOWN-STATION RELATIVE TO THE ALIGNMENT.
 2. NOT ALL WOOD IS SHOWN FOR CLARITY.



SKAGIT COUNTY
PUBLIC WORKS
1800 CONTINENTAL PLACE
MOUNT VERNON, WA 98273-5625
(360) 416-1400



NO.	REVISIONS	DATE
1		
2		
3		
4		
5		
6		
7		
8		
9		
10		
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		
21		
22		
23		
24		
25		
26		
27		
28		
29		
30		

ENGINEER OF RECORD
COUNTY ENGINEER
JON TRISCOL
WASHINGTON
REGISTERED PROFESSIONAL ENGINEER
5403
1/24/15


PROJECT NO.: EO214-5
FED. AID NO.: 4650DRWA #674680
DESIGNED BY: NT
CHECKED BY:
DRAWN BY: DBS
APPROVED BY:
PROJECT LOCATED NEAR:
CONCRETE, WA
S 14 T 34 N R 9 E

CONCRETE SAUK VALLEY ROAD
CULVERT REPAIR PROJECT -
SOUTH OSTERMAN CREEK
CHANNEL SECTIONS (2 OF 3)

1 INCH SCALE BAR
ADJUST SCALE ACCORDINGLY
SHEET
23 OF 30



- NOTES
- ALL SECTION VIEWS ARE ORIENTED LOOKING DOWNSTREAM IN THE CHANNEL AND DOWN-STATION RELATIVE TO THE ALIGNMENT.
 - NOT ALL WOOD IS SHOWN FOR CLARITY.



Natural Systems Design
+ Coastal Geologic Services

CONCRETE SAUK VALLEY ROAD
CULVERT REPAIR PROJECT -
SOUTH OSTERMAN CREEK

CHANNEL SECTIONS (3 OF 3)

1 INCH SCALE BAR
ADJUST SCALE ACCORDINGLY

SHEET
24 OF 30



COUNTY ENGINEER

PROJECT NO.: E0214-S

FED. AID NO.: 4650DRWA #674680

DESIGNED BY: NT

DRAWN BY: DBS

CHECKED BY:

APPROVED BY:

PROJECT LOCATED NEAR:

CONCRETE, WA

S 14 T 34 N R 9 E


NO.	REVISIONS	DATE

SKAGIT COUNTY
PUBLIC WORKS

1800 CONTINENTAL PLACE
MOUNT VERNON, WA 98273-5625
(360) 416-1400


NOTES

1. THE CHANNEL CONSTRUCTION SEQUENCE SHOWN ON THIS SHEET IS A RECOMMENDATION ONLY. ALTERNATE SEQUENCES ARE ACCEPTABLE PROVIDED ALL PROJECT ELEMENTS SHOWN ON THESE PLANS AS DESCRIBED IN THE SPECIAL PROVISIONS.




STEP 1

1. EXCAVATE CHANNEL TO STREAMBED FOUNDATION.
2. PLACE FIVE (5) LONG CHANNEL ROOTWADS AND SIX (6) SHORT CHANNEL ROOTWADS.




STEP 2

1. PLACE APPROXIMATELY 40 TYPE 3 AND TYPE 4 STREAMBED BOULDERS ON STREAMBED FOUNDATION AS DIRECTED BY ENGINEER.




STEP 3

1. PLACE 2' LIFT OF STREAMBED MIX IN CHANNEL, INCORPORATING SLASH MATERIAL.
2. SEAL LIFT BY WASHING IN STREAMBED SAND.




STEP 4

1. INSTALL TWO (2) BANK ROOTWADS.
2. PLACE ONE (1) SHORT CHANNEL ROOTWAD.
3. PLACE 2' LIFT OF STREAMBED MIX ALONG FULL LENGTH OF CHANNEL BED, INCORPORATING SLASH MATERIAL.
4. SEAL LIFT BY WASHING IN STREAMBED SAND.



STEP 5

1. CONSTRUCT LOG TRIANGLES PER DETAIL ON SHEET 26 (RACKING MATERIAL, PILES, AND BOULDER COLLARS NOT SHOWN FOR CLARITY).
2. INSTALL TWO (2) SHORT CHANNEL ROOTWADS.



STEP 6

1. PLACE FINAL LIFT OF STREAMBED MIX, INCORPORATING SLASH MATERIAL, TO MEET FINISH GRADE.
2. SEAL FINAL LIFT BY WASHING IN STREAMBED SAND.
3. INSTALL REMAINING SLASH WATTLES AND BANK ROOTWADS (NOT SHOWN FOR CLARITY) AS REQUIRED IN PLANS.

CHANNEL CONSTRUCTION SEQUENCE


SKAGIT COUNTY
PUBLIC WORKS
1800 CONTINENTAL PLACE
MOUNT VERNON, WA 98273-5625
(360) 416-1400

ENGINEER OF RECORD		COUNTY ENGINEER		NO.		REVISIONS		DATE	
JON TRISCOMI				1/24/19					
REGISTERED PROFESSIONAL ENGINEER									
STATE OF WASHINGTON									
54083									


PROJECT NO.: EO214-S
FED. AID NO.: 4650DRAWA #674680
DESIGNED BY: NT
CHECKED BY: DBS
DRAWN BY: DBS
APPROVED BY:
PROJECT LOCATED NEAR:
CONCRETE, WA
S 14 T 34 N R 9 E

CONCRETE SAUK VALLEY ROAD
CULVERT REPAIR PROJECT -
SOUTH OSTERMAN CREEK
CHANNEL CONSTRUCTION SEQUENCE

1 INCH SCALE BAR
ADJUST SCALE ACCORDINGLY
SHEET
25 OF 30



LOG TRIANGLE PLAN
SCALE: 1" = 5'




LOG TRIANGLE - ISOMETRIC
NTS

CROSS CHAIN LASHING (TYP)


- LOG TRIANGLE NOTES
- LOG TRIANGLE STRUCTURES SHALL BE CONSTRUCTED OF THREE 18" DIA. LOGS WITH INTACT ROOTWADS. SEE TABLE BELOW FOR LOG LENGTH.
 - MEMBER LOGS SHALL BE JOINED BY CROSS CHAIN LASHING AT OVERLAPPING CORNERS. SEE DETAIL SHEET 28.
 - STRUCTURES SHALL BE CONSTRUCTED TO MATCH STAKEOUT LOCATIONS AND ELEVATIONS AT TOP OF CROSSING LOGS, AS INDICATED ON TABLE.
 - DRIVE TWO 14" DIA. 25' LONG (PE-25) VERTICAL PILES AS SHOWN.
 - RACKING MATERIAL (4-10" DIA. X 10-30' LOGS) AND SLASH MATERIAL SHALL BE INTERTWINED WITH LOGS AS STRUCTURES ARE ASSEMBLED. PLACE 15-20 PIECES OF RACKING AND 5 CY OF SLASH PER TRIANGLE. RACKING MATERIAL SHALL BE COVERED AND VOIDS FILLED WITH STREAMBED MIX TO NEATLINES SHOWN ON THESE PLANS.
 - INSTALL ROCK COLLAR WITH TWO TYPE 4 STREAMBED BOULDERS AT EACH CORNER OF STRUCTURE. SEE DETAIL ON SHEET 27.
 - ROCK COLLARS SHALL BE PLACED SUCH THAT THE CONNECTING CHAIN IS TAUT AND IN CONTACT WITH LOGS FORMING TRIANGLE; CONTRACTOR SHALL COUNTERSINK BOULDERS AS NECESSARY TO ACHIEVE INSTALLATION IN THIS MANNER.

ID NO.	LOGS	STAKEOUT	STATION	OFFSET	ELEVATION
T1	3 X 18" DIA. 35' LONG	A	217+95.2	13.1 R	283.7
		B	217+75.0	12.4 R	282.3
		C	217+85.9	10.1 L	282.4
T2	2 X 18" DIA. 35' LONG 1 X 18" DIA. 40' LONG	A	217+74.0	14.8 L	282.6
		B	217+42.3	13.1 L	281.1
		C	217+62.3	7.1 R	281.3
T3	3 X 18" DIA. 35' LONG	A	217+54.4	15.2 R	281.9
		B	217+24.6	13.3 R	280.5
		C	217+42.4	5.8 L	280.7
T4	3 X 18" DIA. 35' LONG	A	217+27.6	16.0 L	280.6
		B	217+08.4	14.5 L	280.1
		C	217+19.7	7.6 R	279.8


NOTE: FOR CLARITY, RACKING MATERIALS NOT SHOWN IN SECTION VIEWS.



SECTION A-A
SCALE: 1" = 5'



SECTION B-B
SCALE: 1" = 5'



SECTION C-C
SCALE: 1" = 5'

ID NO.	LOGS	STAKEOUT	STATION	OFFSET	ELEVATION
T5	3 X 18" DIA. 35' LONG	A	217+00.0	16.0 L	280.0
		B	216+80.7	14.4 L	279.5
		C	216+92.1	7.6 R	279.2
T6	3 X 18" DIA. 35' LONG	A	216+82.0	14.2 R	279.3
		B	216+53.0	12.6 R	278.8
		C	216+68.1	7.4 L	278.5
T7	3 X 18" DIA. 35' LONG	A	216+58.6	15.3 L	279.1
		B	216+36.4	14.8 L	278.6
		C	216+47.7	7.2 R	278.3
T8	3 X 18" DIA. 35' LONG	A	216+33.7	13.4 R	278.6
		B	216+01.4	13.1 R	278.1
		C	216+17.7	6.7 L	277.8

LOG TRIANGLE DETAIL
SCALE: AS NOTED

NSD CGS Natural Systems Design + Coastal Geologic Services

SKAGIT COUNTY
PUBLIC WORKS
1800 CONTINENTAL PLACE
MOUNT VERNON, WA 98273-5625
(360) 416-1400

					DATE
					REVISIONS
					NO.


ENGINEER OF RECORD
COUNTY ENGINEER

PROJECT NO.: EO214-5 FED. AID NO.: 4650DRWA #674680 DESIGNED BY: NT CHECKED BY:	DRAWN BY: DBS APPROVED BY:	PROJECT LOCATED NEAR: CONCRETE, WA S 14 T 34 N R 9 E
--	-------------------------------	--

CONCRETE SAUK VALLEY ROAD
CULVERT REPAIR PROJECT -
SOUTH OSTERMAN CREEK
CHANNEL STRUCTURE DETAILS (1 OF 3)


1 INCH SCALE BAR
ADJUST SCALE ACCORDINGLY

SHEET
26 OF 30




- BOULDER SILL NOTES**
1. TYPE TWO STREAMBED BOULDER. FIVE PER STRUCTURE.
 2. TYPE THREE STREAMBED BOULDER. SIX PER STRUCTURE.
 3. DASHED LINES INDICATE TOP OF BOULDER IS BURIED BENEATH FINISHED STREAMBED ELEVATION.
 4. SET SILL BOULDERS AT SLOPE FROM TOP OF BANK TO THALWEG AND BELOW. INFILL BEHIND SILLS WITH STREAMBED MIX.
 5. BANKWARD $\frac{1}{3}$ OF EACH SILL INCLUDES TWO (2) TYPE THREE AND ONE (1) TYPE TWO STREAMBED BOULDERS PLACED BELOW AND DOWNSTREAM OF THE SILL BOULDERS.
 6. DOWNSTREAM BOULDER SILL. BOULDER SILLS ALTERNATE RIGHT/LEFT ORIENTATION.
 7. STREAMBED BOULDERS SHALL BE PLACED IN CONTACT WITH ONE ANOTHER AND WITH THE DOWNSTREAM BOULDER SILL.

BOULDER SILL DETAIL 1
SCALE: 1" = 5'




- SLASH WATTLE NOTES**
1. CONSTRUCT SLASH WATTLES AS 16-24" DIA. 20' LONG BUNDLES OF RACKING AND SLASH MATERIAL (APPROX. 2-3 CY OF SLASH). SURROUND SLASH WITH 4-6 PIECES OF 4-8" DIA. RACKING MATERIAL AND SECURE SLASH WATTLES WITH A DOUBLE WRAP OF MANILLA ROPE AS NEEDED TO MAINTAIN SHAPE DURING INSTALLATION.
 2. PLACE SLASH WATTLES EMBEDDED HALF THE DIAMETER OF THE WATTLE AND ALIGNED PARALLEL WITH THE TOP OF THE CHANNEL BANK. APPROXIMATE LOCATIONS ARE SHOWN ON THE PLANS; THE ENGINEER WILL DETERMINE AND STAKE FINAL LOCATIONS IN THE FIELD.
 3. ANCHOR SLASH WATTLES WITH TWO PAIRS OF 10" DIA., 15' LONG (PG-15) PILES WITH A PAIR POSITIONED APPROXIMATELY 5' FROM EACH END (FOUR PILES TOTAL). INSTALL ONE PILE VERTICALLY AT THE FACE OF THE WATTLE. INSTALL A SECOND BATTER PILE NEXT TO THE VERTICAL PILE AND AGAINST THE TOP OF THE WATTLE.

SLASH WATTLE DETAIL 3
SCALE: 1" = 4'



BOULDER SILL STAKEOUT			
SILL	STATION	OFFSET	ELEV.
1	219+70.0	8.5 L	292.5
2	219+56.7	8.5 R	291.9
3	219+45.0	8.5 L	291.3
4	219+31.4	8.5 R	290.6
5	219+20.0	8.5 L	290.0
6	219+08.0	8.5 R	289.4
7	218+97.2	8.5 L	288.9
8	218+85.0	8.5 R	288.3
9	218+72.3	8.5 L	287.7
10	218+55.9	8.5 R	286.8
11	218+45.0	8.5 L	286.3
12	218+32.3	8.5 R	285.7
13	218+20.2	8.5 L	285.1
14	218+08.0	9.5 R	284.6


BOULDER SILL MATERIALS	
MATERIAL	COUNT
TYPE TWO STREAMBED BOULDER	5
TYPE THREE STREAMBED BOULDER	6




ROCK COLLAR NOTES

1. THOROUGHLY CLEAN DRILL HOLE AND ALL BONDING SURFACES PRIOR TO APPLICATION OF EPOXY.
2. THE DRILL HOLE SHALL BE FILLED WITH RESIN SUCH THAT WHEN THE EYEBOLT IS INSERTED, A SMALL AMOUNT OF RESIN WILL Ooze OUT OF THE TOP OF THE HOLE. ONCE THE EYEBOLT IS INSERTED IN THE HOLE, IT SHALL NOT BE DISTURBED UNTIL RESIN HAS CURED.
3. BOULDER DIAMETER AVERAGE DIMENSIONS SHOULD TYPICALLY RANGE FROM 3-4 FEET; INDIVIDUAL BOULDER WEIGHT SHALL BE BETWEEN 2,500-4,000 POUNDS.
4. BOULDERS USED TO CONSTRUCT A COLLAR SHALL BE PAIRED AS CLOSELY IN WEIGHT AS POSSIBLE.
5. EACH FULLY CONSTRUCTED COLLAR SHALL BE TESTED TO ENSURE PROPER BONDING BY PICKING UP ONE ROCK ON THE COLLAR AND SUSPENDING THE OTHER. ALL ROCK COLLARS SHALL BE WEIGHED AND FLAGGED WITH WEIGHT.
6. THE LENGTH OF CHAIN SHALL BE DETERMINED IN THE FIELD; LENGTHS ARE ANTICIPATED TO RANGE FROM 4-8 FEET.
7. COMPLETED ROCK COLLAR SHALL HAVE A MINIMUM WEIGHT OF 6,000 POUNDS.

ROCK COLLAR DETAIL 2
SCALE: 1" = 5'



SLASH WATTLE SECTION DETAIL



SAWCUT PILE TOP DETAIL 4
NTS



**Natural Systems Design
+ Coastal Geologic Services**

SKAGIT COUNTY PUBLIC WORKS
1800 CONTINENTAL PLACE
MOUNT VERNON, WA 98273-5625
(360) 416-1400

ENGINEER OF RECORD
COUNTY ENGINEER
JON TRISCOLI
STATE OF WASHINGTON
REGISTERED PROFESSIONAL ENGINEER
54083
1/24/15




PROJECT NO.: EO214-5
FED. AID NO.: 4850DRWA #674680
DESIGNED BY: DBS
CHECKED BY: NT
DRAWN BY: DBS
APPROVED BY:
PROJECT LOCATED NEAR:
CONCRETE, WA
S 14 T 34 N R 9 E

**CONCRETE SAUK VALLEY ROAD
CULVERT REPAIR PROJECT -
SOUTH OSTERMAN CREEK**



CHANNEL STRUCTURE DETAILS (2 OF 3)

1 INCH SCALE BAR
ADJUST SCALE ACCORDINGLY

SHEET
27 OF 30




CROSS CHAIN LASHING DETAIL (2)
NTS 28





TIMBER HANDRAIL DETAIL 4
NTS 28

1. SECURE TAG END OF CHAIN TO TOP LOG TEMPORARILY USING A RAILROAD SPIKE, LARGE FENCING NAIL, OR SIMILAR.
2. WRAP THE CHAIN FULLY AROUND THE BOTTOM LOG THEN ANOTHER HALF WRAP AROUND THE UNDERSIDE OF THE BOTTOM LOG. THEN CROSS OVER THE TOP LOG DIAGONALLY.
3. WRAP CHAIN FULLY AROUND THE BOTTOM LOG THEN ANOTHER HALF WRAP AROUND THE UNDERSIDE OF THE BOTTOM LOG.
4. PULL CHAIN BACK TO THE TAG END SECURED TO THE TOP LOG.
5. SQUARE UP ALL WRAPS AND LOOPS TO REMOVE SLACK PRIOR TO TENSIONING.
6. APPLY TENSION TO THE CHAIN USING MECHANICAL MEANS (CHAIN BINDER, OR SIMILAR); WHILE CHAIN IS FULLY TENSIONED, APPLY QUICK LINK TO CHAIN WHILE TENSIONED THEN SLOWLY RELEASE TENSION.
7. TRIM EXCESS CHAIN.

1. TIMBER HANDRAIL SHALL BE CONSTRUCTED FROM PRESSURE TREATED (GROUND CONTACT RATED) NOMINAL LUMBER.
2. EMBED TIMBER POSTS A MINIMUM OF 2 FEET BELOW THE EXISTING GROUND SURFACE.
3. PITS FOR POSTS SHALL BE NEATLY CREATED, FREE OF DEBRIS AND WATER, AND SHALL MEET THE MINIMUM DIMENSIONS SHOWN ON THIS SHEET.
4. BACKFILL PITS FOR POSTS WITH CONCRETE (MINIMUM 3,000 PSI COMPRESSIVE STRENGTH) AND SHALL HAVE A SLOPING MINIMUM OF 1" ABOVE GROUND.
5. ALLOW CONCRETE TO CURE A MINIMUM OF 24 HOURS PRIOR TO ATTACHING RAILS.
6. CONNECT RAILS TO POSTS WITH GALVANIZED FACE MOUNTED JOIST HANGERS AND MANUFACTURER RECOMMENDED NAILS OR SCREWS.
7. ALL POSTS AND RAILS SHALL BE SIMILAR IN APPEARANCE.



PLANTING AREA LEGEND

-  SLOPE PLANTING AREA (SP)
-  TERRACE PLANTING AREA (TP)

NOTES:

- FOLLOWING COMPLETION OF EARTHWORK AND STRUCTURE PLACEMENT, ALL DISTURBED AREAS SHALL BE SEEDED AND MULCHED ACCORDING TO SHEET 8.
- PLANTING SHALL OCCUR FOLLOWING SEEDING ACCORDING TO THE AREAS SHOWN THIS SHEET AND THE SCHEDULES LISTED ON SHEET 30.
- PLANTING BOUNDARIES SHOWN ON THIS SHEET ARE THE EXPECTED LIMITS OF DISTURBANCE RESULTING FROM THE SOUTH OSTERMAN CREEK PROJECT AND MAY VARY AT THE TIME OF PLANTING. PLANTING BOUNDARIES AND LAYOUT SHALL BE APPROVED BY THE ENGINEER PRIOR TO COMMENCEMENT OF WORK.
- PLANTING SHALL OCCUR AROUND EXISTING STRAW WATTLES, PLACED AS SHOWN ON SHEET 8. STRAW WATTLES SHALL REMAIN.
- NO PLANTING SHALL OCCUR WITHIN 10' OF THE FINISHED EDGE OF PAVEMENT.



Natural Systems Design
+ Coastal Geologic Services

CONCRETE SAUK VALLEY ROAD
CULVERT REPAIR PROJECT -
SOUTH OSTERMAN CREEK

PLANTING PLAN

1 INCH SCALE BAR
ADJUST SCALE ACCORDINGLY

SHEET
29 OF 30

PROJECT NO.: E0214-S

FED. AID NO.: 4650DRAWA #674680

DESIGNED BY: NT

CHECKED BY:

DRAWN BY: DBS

APPROVED BY:

PROJECT LOCATED NEAR:

CONCRETE, WA

S 14 T 34 N R 9 E

COUNTY ENGINEER

ENGINEER OF RECORD



INC.

REVISIONS

DATE

SKAGIT COUNTY
PUBLIC WORKS

1800 CONTINENTAL PLACE
MOUNT VERNON, WA 98273-5625
(360) 416-1400

